



Operating Manual

Bally
MIDWAY™

10601 W. Belmont Ave. • Franklin Park, Illinois 60131 • U.S.A.
Telephone: (312) 451-9200 • Fax No.: 312-451-4150
Cable Address: MIDCO • Telex No.: 72-1596



GAME OH06
MANUAL NO. OH06-00300-0100




DUNGEONS & DRAGONS™ is a trademark owned by and used under license from TSR, Inc. ©1987 TSR, Inc. All Rights Reserved.

Operating Manual

Bally
MIDWAY™

10601 W. Belmont Ave. • Franklin Park, Illinois 60131 • U.S.A.
Telephone: (312) 451-9200 • Fax No.: 312-451-4150
Cable Address: MIDCO • Telex No.: 72-1596



WARNING

**THIS GAME MUST BE GROUNDED. FAILURE TO DO SO MAY
RESULT IN DESTRUCTION TO ELECTRONIC COMPONENTS.**

WARNING: This equipment generates, uses and can radiate radio frequency energy and if not installed and used in accordance with the instruction manual, may cause interference to radio communications. It has been tested and found to comply with the limits for a CLASS A computing device pursuant to SUBPART J of PART 15 of FCC RULES, which are designed to provide reasonable protection against such interference when operated in a commercial environment. Operation of this equipment in a residential area is likely to cause interference in which case the user at his own expense will be required to take whatever measures may be required to correct the interference.

ELECTRICAL BULLETIN: FOR ALL APPARATUS COVERED BY THE CANADIAN STANDARDS ASSOCIATION (CSA) STANDARD C22.2 NO. 1, WHICH EMPLOYS A SUPPLY CORD TERMINATED WITH A POLARIZED 2-PRONG ATTACHMENT PLUG.

CAUTION: TO PREVENT ELECTRIC SHOCK DO NOT USE THIS (POLARIZED) PLUG WITH AN EXTENSION CORD, RECEPTACLE OR OTHER OUTLET UNLESS THE BLADES CAN BE FULLY INSERTED TO PREVENT BLADE EXPOSURE.

ATTENTION: POUR PREVENIR CHOCS ELECTRIQUES NE PAS UTILISER CETTE FICHE POLARISEE AVEC UN PROLONGATEUR. UNE PRISE DE COURANT OU UNE AUTRE SORTIE DE COURANT, SAUF SI LES LAMES PEUVENT ETRE INSEREES A FOND SANS EN LAISSER AUCUNE PARTIE A DECOUVERT.

**USE ONLY GENUINE BALLY MIDWAY
APPROVED REPLACEMENT PARTS.**

©COPYRIGHT MCMLXXXVII BY BALLY MIDWAY MFG. CO. ALL RIGHTS RESERVED.

NO PART OF THIS PUBLICATION MAY BE REPRODUCED BY ANY MECHANICAL, PHOTOGRAPHIC, OR ELECTRONIC PROCESS, OR IN THE FORM OF A PHONOGRAPHIC RECORDING, NOR MAY IT BE TRANSMITTED, OR OTHERWISE COPIED FOR PUBLIC OR PRIVATE USE, WITHOUT PERMISSION FROM THE PUBLISHER. THIS MANUAL IS FOR SERVICE USE ONLY, AND NOT FOR GENERAL DISTRIBUTION. FOR PERMISSION REQUESTS, WRITE: BALLY MIDWAY MFG. CO., 10601 W. BELMONT AVE., FRANKLIN PARK, IL 60131.

Printed in U.S.A.

DUNGEONS & DRAGONS TABLE OF CONTENTS

SECTION 1 INSTALLATION AND GENERAL GAME OPERATION INSTRUCTIONS

DESCRIPTION	PAGE
I. INSTALLATION PROCEDURE	1-1
II. GENERAL GAME OPERATION	1-1
III. TAILORING & TESTING THE GAME	1-2
IV. GAME REGISTERS & OPTIONS	1-4
V. RECOMMENDED 3 & 5 BALL REGISTER OPTION SETTINGS	1-6
VI. TROUBLESHOOTING ON LOCATION	1-7
VII. SOLENOID & SWITCH IDENTIFICATION TABLES	1-10
VIII. LAMP IDENTIFICATION TABLE	1-11
IX. ROUTINE MAINTENANCE ON LOCATION	1-12
X. SWITCH ASSEMBLY ADJUSTMENTS	1-12
XI. SERVICE HINTS	1-12
XII. PANEL TOP PARTS LIST	1-13
XIII. RAMP PARTS, RUBBER RINGS & POSTS LIST	1-14
XIV. FEATURE OPERATION AND SCORING	1-16

SECTION 2 COMPONENT LAYOUTS, SCHEMATICS & WIRING DIAGRAMS

DESCRIPTION	PAGE
WIRING DIAGRAM—CABINET	2-1
WIRING DIAGRAM—PLAYFIELD	2-2
WIRING DIAGRAM—BACKBOX	2-5
6803 PINBALL POWER MODULE P.C. BOARD—COMPONENT LAYOUT	2-9
6803 PINBALL POWER MODULE P.C. BOARD—SCHEMATIC	2-11
6803 CONTROL P.C. BOARD—COMPONENT LAYOUT	2-12
6803 CONTROL P.C. BOARD—SCHEMATIC	2-16
PINBALL SOUND P.C. BOARD—COMPONENT LAYOUT	2-20
PINBALL SOUND P.C. BOARD—SCHEMATIC	2-23
DUAL DISPLAY P.C. BOARD—COMPONENT LAYOUT	2-26
DUAL DISPLAY P.C. BOARD—SCHEMATIC	2-29
BRIGHT-LIGHTS FUSE P.C. BOARD—COMPONENT LAYOUT & SCHEMATIC	2-30
FOUR POSITION EMITTER P.C. BOARD—COMPONENT LAYOUT & SCHEMATIC	2-31
FOUR POSITION DETECTOR P.C. BOARD—COMPONENT LAYOUT & SCHEMATIC	2-32
EPROM LIST	2-33
GLOSSARY OF UNIQUE TERMS & ABBREVIATIONS	2-33

TABLE OF FIGURES

FIGURE	PAGE
I. BLOCK DIAGRAM	ii
Ila. TOP PANEL: SOLENOID & SWITCH IDENTIFICATION	1-10
Ilb. TOP PANEL: LAMP IDENTIFICATION	1-11
Ilc. TOP PANEL: PARTS	1-13
IId. TOP PANEL: RAMP PARTS, RUBBER RINGS & POSTS	1-14
III. DUNGEONS & DRAGONS PINBALL GAME	1-15

BLOCK DIAGRAM—ELECTRONIC PINBALL GAME




FIGURE I.

IMPORTANT NOTICE

**ALL 4 PLAYFIELD BALLS MUST BE INSERTED
IN THE OUTHOLE OR THE BALL TROUGH.**

**THIS GAME WILL NOT START IF THERE IS A
BALL IN THE SHOOTER LANE IN THE GAME
OVER MODE.**

BACKBOX SAFETY WARNING

★ ★ ★ ★ ★ ★ ★ ★
★ **WARNING** ★
★ ★ ★ ★ ★ ★ ★ ★

**TO AVOID INJURY TO OWNER/SERVICE PERSONNEL AND TO PREVENT
DAMAGE TO THE MACHINE, THE BACKBOX MUST BE SECURED WITH
THE BOLTS PROVIDED BEFORE THE MACHINE IS TRANSPORTED OR
ACTIVATED.**

M051-00365-A063

DETACHING OF PINBALL GAME BACKBOX

When the Backbox is in an upright position and the 3/8" hold-down bolts are removed, the Backbox can be removed from the Main Cabinet by lifting the right corner of the Backbox (about 3/4") and pulling it slightly towards you. Now both hinges are disengaged and the Backbox can be removed.

OPTIONAL BACKBOX MODIFICATION NOTICE

Two (2) BACKBOX ACCESS HOLE COVERS, part # 0H06-99138-0000, and six (6) #6 X 3/8" PHILLIPS ROUND-HEAD WOOD SCREWS, part # 0017-00101-0398, are provided in this Game's SPARE PARTS KIT ASSEMBLY, part # AH06-00032-0000. Refer to pages 7 and 52 in the DUNGEONS & DRAGONS PARTS MANUAL, # AH06-00300-0200, for parts identification.

When the game's Top Box is removed from the Backbox for any reason, each Backbox Access Hole Cover must be secured over each access hole in the top panel of the Backbox by using three (3) wood screws. Ensure that both access holes are completely covered.

SECTION 1

I. INSTALLATION PROCEDURE

First, bolt the legs to the Cabinet. Second, feed the line cord between the Backbox and the Cabinet, then mount the Backbox and secure it with the bolts provided in the spare parts kit.

On all games, there are certain items that should be checked after shipment, and they are:

1. Check that all cable connectors are completely seated on printed circuit board assemblies.
2. Check that all cables are clear of moving parts.
3. Check for wires that may have come loose during shipment.
4. Check switches for loose solder or other foreign material that may have come loose in shipment and could cause shorting of switches or lamp sockets.
5. Check coils for proper soldering. Cold solder connections may not show up in factory inspection, but vibration in shipment may break the contacts.
6. Check that fuses are firmly seated and making good contact.
7. Check and adjust the plumb bob tilt on the left side of the Cabinet.
8. Check wiring of the plug on the transformer to correspond to location voltage. FOR REFERENCE, SEE BACKBOX WIRING SCHEMATIC ON PAGE 2-5.

For 115 VAC, install jumper wires 2-8, 3-6 and 7-10.

For 120 VAC, install jumper wires 2-8, 4-6 and 7-11.

For 220 VAC, install jumper wires 4-8 and 7-9.

For 240 VAC, install jumper wires 4-8 and 7-11.

9. Place the four (4) game balls into the Playfield outhole.
10. Plug in the line cord.

II. GENERAL GAME OPERATION

Move the ON/OFF switch at the bottom right front corner of the Cabinet to the "ON" position. The game will play a power-up sound sequence and reset the drop targets. If any switches are stuck, stuck switch information is displayed at this time. After a short delay, "1-4 can play" on the display will indicate that the game is ready to play. The game should accept coins and post the appropriate credits. Pressing the credit button on the Cabinet will cause the outhole kicker to serve the ball to the shooter alley. A game-up sound sequence is played to announce play-readiness.

Each time the credit button is pressed, it posts one player and the credits are reduced by one. Shooting the ball initiates play.

The game awards all points earned by the player. If a spinner is turned and scoring when the ball hits a target, the spinner and the target scores are awarded.

When the ball enters the outhole, the bonus score is added to the total score. The player-up and/or ball in play is advanced one position. The outhole kicker serves the ball to the shooter alley and play is resumed. This continues until each player has played the allowable number of balls per game. At this time, a random Match number appears in the display. If the number is the same as in a player's score, a free credit game is awarded.

An extra ball won during the course of the game are played immediately after the player's regular ball enters the outhole. The player-up and/or ball in play are not advanced before the game serves the extra ball for play.

Slamming the machine results in a Game Over condition. This causes all feature lights to go out (the game goes "dead") and a time delay occurs. This occurs anytime either one of the slam switches make contact. This is to discourage unnecessary abuse to the game. After the delay, "1 to 4 can play" is displayed followed by the power-up sound sequence.

Any number of slam switches could be installed by the operator, to meet his/her individual requirements. The switch should be adjusted to have approximately 1/16" gap between the contacts. The weighted blade should be adjusted to attain the desired sensitivity. Decreasing the gap between contacts will make the switch more sensitive. Opening the gap will reduce sensitivity.

If at the end of the game either the "High Score to Date" is beaten or if the score is over 10,000,000, free games will be awarded according to the "High Score to Date" register setting.

Tilting the game results in the loss of the ball in play. Bonus points are not scored. The flippers, thumper bumpers, etc. go 'dead'. The purpose of the tilt penalty is to discourage the player from jostling the machine in an attempt to prolong game play. Game action returns to normal after the ball kicker assembly serves the ball to the shooter alley.

NOTE: These are general instructions. Therefore, if a spinner or drop target is not used on your specific pinball game, please disregard any operating instructions related to these devices.

III. TAILORING & TESTING THE GAME

INTRODUCTION

We at Bally/Midway are very proud to introduce our new system which not only provides more information to the operator but it also communicates with the player thru the use of alphanumerics in the display.

It was our aim to design a system which could be used without a manual. This will come to light the moment you press the Self-test button and the displays come to life with their messages of assistance. This allows you to change game features, awards and threshold settings and monitor specific special awards, game percent and income just by reading what is displayed. The registers are now described with useful titles much as "Bookkeeping Data" or "Self-Testing."

If you've ever changed the replay thresholds on a machine and you forgot to change the replay card because you were distracted by a customer, listen to this: "It will never happen again!" When you change this replay threshold to 2,000,000 in "Percent Options," the corresponding message "First Replay at 2,000,000" will be displayed in the Game Over mode.

OPERATION

The keyboard is located on the right inside wall of the game near the front door. The cable is long enough, so that once the keyboard is removed, it may be operated from outside the machine. **Note:** The keypad is mounted with a 1/4" Hex screw for shipping purposes.

1. Press the Test button located on the front door. This tells the processor to do the following:
 - A. It checks the switches wired in parallel with the keypad.
If any switches are closed, the game automatically jumps to the Stuck Switch Test and displays a stuck switch message.
 - B. If there were no stuck switches you will be welcomed with "Bally's Testing Is Easy As ABC."
2. When the appropriate heading appears on the backglass display, press "ENTER" on the keypad once. Within each heading, there are categories which are operator selectable. When the appropriate category appears on the backglass display, press "ENTER" once to access that category.
3. Set your registers with the keypad.
4. Press "ENTER" again to advance to the next category setting. Press "CLR" to re-start the Self-Test routine. Press "GAME" to lock-in the option settings.

STEPPING THROUGH

To choose a category quickly once the Test Mode has been selected, use the "A" button to advance to the desired category. If you pass by the category you desired, use the "B" button to back-up to the appropriate position. Once you read the category desired, press the "ENTER" button to select that topic. The display will now show the first item in that category.

Again, use the "A" and "B" buttons to select the next item you wish to look at or change. The "A" button allows you to advance to the end of a category and then out to the next category. The "B" button allows you to advance backwards in the same manner. **Please note:** When in the Self-Test category, the display will cycle automatically from one test to the next. Because the "A", "B", and "C" buttons are used for different functions in this category, they cannot be used to advance from one test to another test. To exit a test in this category, just press the "ENTER" button & advance to the next test.

SELF-PERCENTAGING

1. The term Self-Percentaging refers to the game's ability to automatically adjust the score level of Threshold 1 to attain a desired replay percentage, also known as the TARGET PERCENT. (See step #8 on page 1-3).
2. Self-Percentaging also applies to extra balls, when used instead of replays.
3. Initially, a minimum of 200 games must be played before the Self-Percentaging Process goes into effect. It then monitors the current replay percentage of Threshold 1 ONLY and makes an adjustment, if necessary, every 50 games.
4. The Self-Percentaging Process will automatically adjust the score level of Threshold 1 ONLY. It makes NO adjustments to OTHER "Award" features in the game.

5. Located within the "PERCENT OPTIONS" category of your game's test mode are the following registers:

- THRESHOLD 1
- SELF PERCENT
- TARGET PERCENT
- THRESHOLD 1 PERCENT

Each of these registers are explained in detail further in this text.

6. To set or check the current score level of Threshold 1:

- A. "Step through" your game's test mode, using the "A" or "B" button on the keypad, until you reach the category titled: "PERCENT OPTIONS."
- B. Press the "ENTER" button to select this category.
- C. The first register displayed will be THRESHOLD 1.

THRESHOLD 1—This register displays the current score level of the 1st Replay Threshold. Enter any value from 0 to 9,999,999 to set the desired score level.

7. To activate the Self-Percentaging Process:

- A. "Step through" your game's test mode, using the "A" or the "B" button on the keypad, until you reach the category titled: "PERCENT OPTIONS."
- B. Press the "ENTER" button to select this category.
- C. Again, use the "A" button to "step through" until you reach a register titled: "SELF PERCENT."

SELF PERCENT—This register displays whether the Self-Percentaging Process is OFF or ON. Enter "0" to turn OFF or "1" to turn ON.

8. To adjust the desired Replay Percentage for Threshold 1:

- A. "Step through" your game's test mode, using "A" or "B" button on the keypad, until you reach a category titled "PERCENT OPTIONS."
- B. Press the "ENTER" button to select this category.
- C. Again, use the "A" button to "step through" until you reach the register titled: "TARGET PERCENT."

TARGET PERCENT—This register displays the desired percentage of replays to be awarded for reaching Threshold 1. For example, if you want Threshold 1 to award a replay in 15% of the games played, you would press keys "1," "5," and then "ENTER." This register will then display "15%" as your goal or "TARGET PERCENT."

NOTE: This register automatically defaults to a factory setting of "10%," when the "FACTORY RESET" register is enabled.

9. The TOTAL Replay Percentage will be 10% or 15% higher with the addition of Match, Special and High Score to Date credits.

10. To manually check the current Replay Percentage of Threshold 1 only:

- A. "Step through" your game's test mode, using the "A" or "B" button on the keypad, until you reach a category titled: "PERCENT OPTIONS."
- B. Press the "ENTER" button to select this category.
- C. Again, use the "A" button to "step through" until you reach the register titled: "THRESHOLD 1 PERCENT."

THRESHOLD 1 PERCENT—The figure displayed in this register is the actual percentage of replays awarded for reaching Threshold 1. Progress of the Self-Percentaging Process may be monitored by comparing the current value displayed in this register with the "TARGET PERCENT."

11. The size of adjustment, made by the Self-Percentaging Process to the score level of Threshold 1, is determined by the current difference between the "TARGET PERCENT" (entered by the operator) and the actual percentage of replays awarded for reaching Threshold 1.

- A difference of 10% or more will result in a 10% adjustment.
- A difference equal to or greater than 5%, but less than 10%, will result in a 5% adjustment.
- A difference less than 5% will result in a 1% adjustment.

12. To check the current score level of Threshold 1, refer to step #6 above.

13. When the "CLEAR BOOKKEEPING" register is enabled, the Self-Percentaging Process is re-initiated.

IV. DUNGEONS & DRAGONS— GAME REGISTERS & OPTIONS

BOOKKEEPING DATA

TOTAL COINS	Number Of Coins Thru Chutes 1, 2, & 3
GAME PERCENT	Percentage Of Replays
COINS CHUTE 1	# Of Coins Thru Chute 1
COINS CHUTE 2	# Of Coins Thru Chute 2
COINS CHUTE 3	# Of Coins Thru Chute 3
BONUS CREDITS	Number Of Bonus Credits Given
TOTAL PLAYS	Number Of Plays Both Paid And Replays
TOTAL REPLAYS	Number Of Awarded Games
SERVICE METER	Total # Of Service Credits
GAME CREDITS	Current Game Credits—Enter 0 thru 5. Credits are added to Service Meter. These credits are <u>NOT</u> added to current Game Credits.
	Total # Of Playfield Specials Awarded
SPECIAL METER	To clear bookkeeping data, press "65" & then press "ENTER."
CLEAR BOOKING	

SELF-TESTING

SINGLE LAMP

Lights one lamp at a time and also displays SCR (Lamp Driver) number and connector ID. Press "A" to advance, "B" to back-up and "C" to cycle.

ALL LAMPS

All lamps light alternately; first displaying "A" phase and then "B" phase.

DISPLAY

Steps thru alphanumeric character set.

SOLENOID

Energizes one solenoid at a time, then displays solenoid driver number and connector ID.

SINGLE SOLENOID

Energizes one solenoid at a time. Press "A" for same solenoid. Press "B" for next solenoid.

SOUND

Plays game sounds.

GAME ROM ID

Displays ROM or ROM's ID.

SWITCH TEST

Displays stuck switch by description.

NOTE: PRESS TEST BUTTON ON DOOR TO EXIT SWITCH TEST.

PERCENT DATA VALUES

GAME PERCENT	Percentage Of Replays
TOTAL PLAYS	Number Of Plays Both Paid And Replays
GAME TIME	Total Number Of Minutes
TOTAL REPLAYS	Total Number Of Replays
THRESHOLD 1	# Of Times The Point Total Exceeded The First Threshold Level
THRESHOLD 2	# Of Times The Point Total Exceeded The Second Threshold Level
THRESHOLD 3	# Of Times The Point Total Exceeded The Third Threshold Level
HI-SCORE BEATEN	# Of Times The Point Total Exceeded The High Score
FREE BALLS	# Of Extra Balls Awarded
SPECIAL	Not Used
TIMES MULTI	# Of Times Multi-Ball Play Was Achieved

PERCENT OPTIONS

THRESHOLD 1

Enter 0 thru 9,999,999 to set award level and display.

SELF PERCENT

Enter 0 or 1; 0 Disables Self-Percentaging Process and 1 Enables Self-Percentaging Process.

TARGET PERCENT

Enter desired percentage of replays awarded for reaching Threshold 1.

THRESHOLD 1 PERCENT

Displays actual percentage of replays awarded for reaching Threshold 1.

THRESHOLD 2

Enter 0 thru 9,999,999 to set award level and display.

THRESHOLD 3

Enter 0 thru 9,999,999 to set award level and display.

HIGHEST SCORE

Enter 0 thru 9,999,999 to set the Hi-Score replay level.

BASIC OPTION VALUES

CREDIT LIMIT

Enter 1 thru 40.

BALLS PER GAME

Enter 1 thru 5.

THRESHOLD MODE

Enter 0 thru 3; 0=0, 1=Points, 2=Extra Balls, & 3=Replays.

SPECIAL MODE

Enter 0 thru 3; 0=0, 1=Points, 2=Extra Balls, & 3=Replays.

HI-SCORE MODE

Enter 0 thru 3; 0=0, 1=1 Replay, 2=2 Replays, & 3=3 Replays.

SOUND MODE

Enter 0 thru 3; 0=Chimes W/O Background,
1=Chimes With Background,
2=Sounds W/O Background, &
3=Sounds With Background.

GERMAN PRIZE

German Meter

MATCH OPTION

Enter 0 or 1; 0 Disables Match and 1 Enables Match.

CREDIT DISPLAY

Enter 0 or 1; 0=No Credits Displayed & 1=Credits Displayed.

NO LIMIT REPLAYS

Enter 0 or 1; 0=Only 1 Award Per Game & 1=More Than 1 Per Game.

FREE PLAY

Enter 0 or 65; 0=Coins and 65=Free Play.

SLINGSHOT

Enter 0 or 1; 0=No Slingshots and 1=Slingshots.

TILT WARNING

Enter 0 thru 3; 0=No Warning, 1=1 Warning, 2=2 Warnings, & 3=3 Warnings.

FACTORY SETTINGS

1,750,000

1

10

Unchanged

4,500,000

00

5,999,999

10

3

3

3

3

3

0

1

1

1

0

1

1

FEATURE OPTIONS

RESET FACTORY	Enter 65 for factory selected scores and features.			
RECALL TARGETS	Enter 0 or 1; This entry recalls DUST targets, SHIELD targets & SWORD targets. *0 = No Memory 1 = Memory			
X-BALL TIMER	Enter 0 thru 3; This entry controls length of time allowed to collect EXTRA BALL.			
	<u>ENTER</u>	<u>LENGTH OF TIME</u>	<u>ENTER</u>	<u>LENGTH OF TIME</u>
	0	4 seconds	2	10 seconds
	*1	6 seconds	3	16 seconds
DUNGEON TIMER	Enter 0 thru 3; This entry controls the length of time a particular DUNGEON LEVEL (or playfield multiplier) value is held before reverting to next lower value.			
	<u>ENTER</u>	<u>LENGTH OF TIME</u>	<u>ENTER</u>	<u>LENGTH OF TIME</u>
	0	10 seconds	2	40 seconds
	*1	20 seconds	3	60 seconds
RETAIN BALLS	Enter 0 thru 2; When game is over: 0 = One or both Teleport Drop Targets will eject held ball. *1 = One Teleport Drop Target retains ball & other Teleport Drop Target ejects ball. 2 = Both Teleport Drop Targets retain held balls.			
MULTI-BALL SAVERS	Enter 0 or 1; This entry controls whether or not the AUTO SAVER feature, for both MAGIC-SAVE lanes is activated each time multi-ball is achieved. *0 = No AUTO SAVER 1 = AUTO SAVER			
AUTO SAVER	Enter 0 thru 3; This entry controls level of game points beyond which AUTO SAVER feature is disabled.			
	<u>ENTER</u>	<u>LEVEL OF GAME POINTS</u>	<u>ENTER</u>	<u>LEVEL OF GAME POINTS</u>
	0	None	*2	200,000
	1	100,000	3	300,000
GATE ON TIMER	Enter 0 thru 7; This entry sets <u>initial</u> length of time (for each player) either Ball Saver gate remains closed after being <u>manually</u> activated. During game, this time length is also controlled by Control Gate Time Option. See note below.			
	<u>ENTER</u>	<u>LENGTH OF TIME</u>	<u>ENTER</u>	<u>LENGTH OF TIME</u>
	0	0.83 Second	*4	1.50 Seconds
	1	1.00 Second	5	1.66 Seconds
	2	1.16 Seconds	6	1.83 Seconds
	3	1.33 Seconds	7	2.00 Seconds
CONTROL GATE TIMER	Enter 0 thru 7; For each player, this entry controls length of time (along with Gate On Timer Option), either Ball Saver gate remains closed after being manually activated. See note below.			
	<u>ENTER</u>	<u>BALL SAVER GATE ACTIVATED</u>	<u>ENTER</u>	<u>BALL SAVER GATE ACTIVATED</u>
	0	6 Times	4	14 Times
	1	8 Times	5	16 Times
	*2	10 Times	6	18 Times
	3	12 Times	7	20 Times
ATTRACT SOUND	Enter 0 thru 1; After game is over, this entry enables or disables ATTRACT SOUND mode while displaying Hi-Scores and instructions. 0 = No Attract Sound *1 = Attract Sound			

*Factory Setting .

NOTE: The Gate On Timer is initialized for each player at the beginning of the game (see the Gate On Timer Option above). The game counts the number of times the Ball Saver gates are activated by a particular player. If a match is found when compared to the number of times allowed, as set in the Control Gate Timer Option, the next lower time setting in the Gate Timer Option is selected. This information does not apply to the AUTO SAVER feature.

PRICING OPTIONS

CHUTE 1 OPTIONS

XX coin for yy credit; Coins (xx) will flash first. Enter 1 thru 99 coins. Next, the credits (yy) will flash. Enter 1 thru 10 credits. Then coins (xx) will flash again. Either press "ENTER," if the values are correct, or repeat the data entry.

CHUTE 1 BONUS; Enter 0 thru 40; 0 = No Awarded Bonus Credit and 1 thru 40 = The Number Of Credits At Which 1 Bonus Credit Will Be Awarded

CHUTE 2 OPTIONS

XX coin for yy credit; Coins (xx) will flash first. Enter 1 thru 99 coins. Next, the credits (yy) will flash. Enter 1 thru 10 credits. Then coins (xx) will flash again. Either press "ENTER," if the values are correct, or repeat the data entry.

CHUTE 2 BONUS; Enter 0 thru 40; 0 = No Awarded Bonus Credit and 1 thru 40 = The Number Of Credits At Which 1 Bonus Credit Will Be Awarded

CHUTE 3 OPTIONS

XX coin for yy credit; Coins (xx) will flash first. Enter 1 thru 99 coins. Next, the credits (yy) will flash. Enter 1 thru 10 credits. Then coins (xx) will flash again. Either press "ENTER," if the values are correct, or repeat the data entry.

CHUTE 3 BONUS; Enter 0 thru 40; 0 = No Awarded Bonus Credit and 1 thru 40 = The Number Of Credits At Which 1 Bonus Credit Will Be Awarded

Example:

To set Coin Chute 1 for 3 credits/2 coins (with no credits delivered on the first coin):

1. CHUTE 1 OPTIONS: Enter 02 coin for 03 credit.

2. CHUTE 1 BONUS: Enter 00.

To set Coin Chute 1 for 3 credits/2 coins (with one credit delivered on the first coin and two credits delivered on the second coin):

1. CHUTE 1 OPTIONS: Enter 01 coin for 01 credit.

2. CHUTE 1 BONUS: Enter 02.

If all 3 Chute Options and Bonus Registers are set the same, then all Chutes will work "together."

V. RECOMMENDED 3 & 5 BALL OPTION SETTINGS

	3-BALL	5-BALL
REPLAYS		
Special Mode	3	3
Match Option	1	1
High Score Mode	3	3
1st replay at	1,750,000	3,500,000
2nd replay at	4,500,000	7,000,000
X-BALL		
Special Mode	2	2
Match Option	0	0
High Score Mode	0	0
1st Extra Ball at	1,750,000	3,500,000
2nd Extra Ball at	4,500,000	7,000,000
NOVELTY		
Special Mode	1	1
Match Option	0	0
High Score Mode	0	0
HIGH GAME TO DATE (reset periodically)		
3-BALL	5,999,999	5-BALL 9,999,999

DUNGEONS & DRAGONS OPTION SETTINGS

	3-BALL	5-BALL
FEATURE OPTIONS		
REGISTER		
RECALL TARGETS	0	1
X-BALL TIMER	1	0
DUNGEON TIMER	2	0
RETAIN BALLS	1	0
MULTI-BALL SAVERS	1	0
AUTO SAVER	2	1
GATE ON TIMER	4	4
CONTROL GATE TIMER	2	2
ATTRACT SOUND	1	1
In Basic Options:		
SLINGSHOT	1	1
TILT WARNING	1	1

VI. TROUBLESHOOTING ON LOCATION

SYMPTOM: GAME WON'T POWER-UP.

Game does not play power-up tune when power is turned on and the general illumination lamps are lit.

ACTION:

- A. Check fuses on Power Module.
- B. Turn power OFF. Open Backbox. Locate light emitting diode (LED) on 6803 Control Board.
- C. Turn power ON. LED must flash 9X to indicate that the Control Board is good. Correct sequence is flash-pause-flash and then seven more flashes and then the LED goes out.
- D. If LED does not come on or does not flash, or flashes, but less than 9X, turn off power. Check fuses. If fuses are good, replace the 6803 Control Board.

CAUTION: Replacement Control Board must have same Part Number or incorrect operation will result! See Parts List for Control Board on pages 2-13 thru 2-15 and EPROM Listing on page 2-33.

Turn power ON.

- E. If game is correct, it is now ready for play. If game is not correct, contact the Bally-Midway Service Department.

SYMPTOM: LAMPS ARE ALWAYS ON OR ALWAYS OFF DURING GAME PLAY.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Lamp Tests with keyboard. If game is correct all feature lamps flash ON and OFF.
- B. Carefully raise playfield or open backbox to gain access to lamps.
- C. Replace bulbs that do not flash.
- D. If game is correct, it is now ready for play.
- E. If game is not correct, turn power OFF. Replace 6803 Control Board. Turn power ON and repeat step A.
- F. If game is correct, it is now ready for play. If game is not correct, contact Bally-Midway Service Department.

SYMPTOM: DISPLAYS

- I. Display digits improper on one or several, but less than all Display Driver Module(s). Improper: One or several segments always OFF, digits mottled (spotted), or several segments or digit(s) always ON.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Display Test with keyboard. If the game is correct, each digit on each Display displays the numbers 0 through 9 and the alphabet in all 7 digit positions in all displays. Note defective Display Driver Modules.
- B. Turn power OFF.

WARNING: High Voltage is supplied to the Display Driver Modules from the Power Module. Wait a minimum of 30 seconds for High Voltage to bleed off before servicing modules.

- C. Replace Display Driver Module(s). Turn power ON. Repeat step A.
 - D. If game is correct, it is now ready for play. If game is not correct, contact Bally-Midway Service Department.
- II. All displays improper. Digit(s) are always ON or OFF/segment(s) are always ON or OFF on all displays.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Display Test with keyboard. If the game is correct, each digit on each Display displays the numbers 0 through 9 and the alphabet in all 7 digit positions. Note defective Display Driver Modules.
- B. Replace 6803 Control Board. Turn power ON. Repeat step A.

CAUTION: Replacement Control Board must have same Part Number or incorrect operation will result! See Parts List for Control Board on pages 2-13 thru 2-15 and EPROM Listing on page 2-33.

- C. If game is correct, it is now ready to play. If game is not correct, contact Bally-Midway Service Department.

III. One or several displays always OFF.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Display Test with keyboard. If the game is correct, each digit on each Display displays the numbers 0 through 9 and the alphabet in all 7 digit positions. Note defective Display Driver Modules.
- B. Turn power OFF.
- C. Replace Display Driver Module(s). Turn power ON. Repeat step A.
- D. If game is correct, it is now ready for play. If game is not correct, contact Bally-Midway Service Department.

SYMPTOM: SOLENOIDS

I. One or more solenoids do not pull-in during game play.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Solenoid Test with keyboard.
- B. If game is correct, each solenoid should be energized in sequence. The solenoid name appears with the Driver (Q) Number and connector jack with pin numbers. (NOTE: If most of the Playfield Solenoids DO NOT operate, check the Playfield Fuse to see if it is blown. It is generally found near the Flipper Assemblies on the bottom of the Playfield.)
- C. Carefully lift the Playfield to gain access to the solenoid. Turn power OFF. Inspect the solenoid.
- D. If a lead is broken off, repair. Repeat steps A & B. If game is correct, it is now ready for play. If solenoid wiring was correct, turn power OFF.
- E. Replace 6803 Control Board. See CAUTION NOTE on page 1-7.
- F. Repeat steps A & B. If game is correct, it is now ready to play. If game is not correct, turn power OFF.
- G. Replace Sound Module A8.
- H. Repeat steps A & B. If game is correct, it is now ready to play. If game is not correct, contact the Bally-Midway Service Department.

II. Solenoid(s) always energized. **NOTE:** If momentary solenoids (ball ejects, slingshots, thumper-bumpers, etc.) are energized continuously, they are subject to damage. Limit troubleshooting to one minute with power ON, followed by **five minutes with power OFF**. Repeat as necessary. Replace damaged solenoids. **NOTE:** When troubleshooting Playfield Solenoid Circuits, be advised that a constantly energized Solenoid (i.e. Thumper-Bumper) will blow the Playfield Fuse in a few seconds. To avoid replacing the Playfield Fuse repeatedly, try to isolate the faulty Solenoid Circuit as soon as the game power switch is flipped ON.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Solenoid Test with keyboard.
- B. If game is correct, each solenoid should be energized in sequence. The solenoid name appears with the Driver (Q) Number and connector jack with pin numbers. **NOTE:** If most of the Playfield Solenoids DO NOT operate, check the Playfield Fuse to see if it is blown. It is generally found near the Flipper Assemblies on the bottom of the Playfield.
- C. Carefully lift the Playfield to gain access to the solenoid. Turn power OFF. Inspect the solenoid.
- D. If a lead is broken off, repair. Repeat steps A & B. If game is correct, it is now ready for play. If Solenoid wiring was correct, turn power OFF.
- E. Replace 6803 Control Board. See CAUTION NOTE below.
- F. Repeat steps A & B. If game is correct, it is now ready to play. If game is not correct, turn power OFF.
- G. Replace Sound Module A8.
- H. Repeat steps A & B. If game is correct, it is now ready to play. If game is not correct, contact the Bally-Midway Service Department.

SYMPTOM: NO SOUND

ACTION:

- A. With power ON, open front door. Select SELF TEST-Sound Test with the keyboard.
- B. Turn volume control clockwise to the maximum position.
- C. If correct, sound will be heard. If incorrect, try seating speaker lead connector (J2) and input connector (J1) on the Sound Board.
- D. If correct, sound will be heard. If incorrect, contact the Bally-Midway Service Department.

SYMPTOM: SWITCHES

Feature (Drop Targets, Stand-up Targets, etc.) does not score.

ACTION:

- A. With power ON, open front door. Select SELF TEST-Switch Test with the keyboard.
- B. If the game is correct, "All Switches Open" is displayed. Otherwise, the name of the switch(es) will be displayed with jack and pin numbers.
- C. Carefully lift the Playfield. Locate the switch assembly identified from the display. Visually inspect the switch assembly. If the contacts are stuck, re-gap them to 1/16". Repeat steps A & B. If the game is correct, it is now ready to play. If the game is not correct, turn power OFF.
- D. Replace the 6803 Control Board.
- E. Repeat steps A & B. If game is correct, it is now ready to play. If game is not correct, contact the Bally-Midway Service Department.

CAUTION: Replacement 6803 Control Board must have same Part Number or incorrect operation will result! See Parts List for Control Board on pages 2-13 thru 2-15.

SUBJECT: 6803 CONTROL BOARD POWER-UP TEST SEQUENCE

The following is an abbreviated self-test routine for the 6803 Control Board.

1st Flash—Determines if the internal RAM U1 is good. (6803)

2nd Flash—Checks to see if the program ROM U2 is good. (27128)

3rd Flash—Checks to see if the program ROM U3 is good. (27128)

4th Flash—Checks the C-MOS RAM U4. (6116P-3)

5th Flash—Tests U8 PIA-0. (6821)

6th Flash—Tests U7 PIA-1. (6821)

7th Flash—Checks the internal display interrupt generator U1. (6803)

8th Flash—Verifies U12 and U8 operation of the phase B switched illumination voltage. NOTE: Fuse F5 on the Power Module provides the phase B signal to the Control Board for U12 and U8.

9th Flash—Verifies U1, U11, and U12 operation of the phase A switched illumination voltage. NOTE: Fuse F4 on the Power Module provides the phase A signal to the Control Board for U1, U11, and U12.

SUBJECT: SOUND BOARD SELF-TEST SEQUENCE

The following is an abbreviated self-test routine for the 6809 Sound Board.

1st Flash—Determine if the external ROM U7 is good.

2nd Flash—Checks to see if the external RAM U6 is good.

3rd Flash—Checks the PIA U8.

The following is an abbreviated self-test routine for the Sounds Deluxe (68000) Board:

1st Flash—Determines if the ROM U11 is good.

2nd Flash—Determines if the ROM U12 is good.

3rd Flash—Determines if the ROM U13 is good.

4th Flash—Determines if the ROM U14 is good.

5th Flash—Checks to see if the RAM U9 and U10 is good.

6th Flash—Checks the PIA U7.

VII OH06 DUNGEONS & DRAGONS

□ SOLENOID IDENTIFICATION TABLE

SELF TEST #	SEQUENCE
1	TOP THUMPER BUMPER
2	LEFT THUMPER BUMPER
3	RIGHT THUMPER BUMPER
4	BOTTOM THUMPER BUMPER
5	LEFT SLINGSHOT
6	RIGHT SLINGSHOT
7	RESET DROP TARGET
8	KICKER LEFT
9	KICKER RIGHT
10	TELEPORT LEFT
11	TELEPORT RIGHT
12	KICK TO PLAYFIELD
13	RESERVED FOR GERMAN USE
14	OUTHOLE
15	KNOCKER
16	FLEXSAVE RIGHT (RIGHT GATE)
17	FLEXSAVE LEFT (LEFT GATE)
18	FLIPPER

○ SWITCH ASSEMBLY IDENTIFICATION TABLE

SELF TEST #	SEQUENCE
1	DUST 1 LEFT (TARGET)
2	DUST 2 (TARGET)
3	DUST 3 (TARGET)
4	DUST 4 RIGHT (TARGET)
5	CABINET LEFT
6	CREDIT (CABINET)
7	CABINET RIGHT
8	OUTHOLE
9	COINS RIGHT (DOOR)
10	COINS LEFT (DOOR)
11	COINS MIDDLE (DOOR)
12	LEFT RETURN LANE
13	RIGHT RETURN LANE
14	SLAM (DOOR)
15	TILT (CABINET)
16	REBOUND
17	TOP BUMPER
18	LEFT BUMPER
19	RIGHT BUMPER
20	BOTTOM BUMPER
21	LEFT SLINGSHOT (X2)
22	RIGHT SLINGSHOT (X2)
23	DRAGON LAIR LEFT
24	DRAGON LAIR RIGHT
25	SHIELD 1 LEFT (TARGET)
26	SHIELD 2 MIDDLE (TARGET)
27	SHIELD 3 RIGHT (TARGET)
28	SWORD 1 LEFT (TARGET)
29	SWORD 2 MIDDLE (TARGET)
30	SWORD 3 RIGHT (TARGET)
31	TELEPORT LEFT EMPTY
32	TELEPORT LEFT LOADED
33	DROP TARGET BOTTOM
34	DROP TARGET MIDDLE
35	DROP TARGET TOP
36	SKILL 1 BOTTOM
37	SKILL 2 MIDDLE
38	SKILL 3 TOP
39	TELEPORT RIGHT EMPTY
40	TELEPORT RIGHT LOADED
41	LEFT RETURN LANE
42	LEVEL SWITCH
43	MILLION SWITCH
44	RESTORE WEAPONS
45	NOT USED
46	OUTHOLE 1 LEFT
47	OUTHOLE 2 MIDDLE
48	OUTHOLE 3 RIGHT

*NOTE: SEQUENCE NUMBERS SHOWN HERE ARE USED AS AN AID IN LOCATING FACULTY SOLENOID OR SWITCH ON FIGURE 11a.

*NOTE: BALL EJECT VECTOR SHOWN FOR EACH TELEPORT DROP TARGET ASSEMBLY. BALL WILL EXIT AS INDICATED ON FIGURE 11a.






FIGURE 11 a

VIII FEATURE LITES IDENTIFICATION TABLE



THESE FEATURE LAMPS 32 35 67 68 69
ARE LOCATED IN THE TOP BOX.




FIGURE II b

SEQUENCE	DESCRIPTION
1	SHIELD 1 LEFT
2	SHIELD 2 MIDDLE
3	SHIELD 3 RIGHT
4	SWORD 1 LEFT
5	SWORD 2 MIDDLE
6	SWORD 3 RIGHT
7	EXTRA LIFE (BACK PANEL)
8	FLAME 20K
9	FLAME 19K
10	FLAME 18K
11	FLAME 17K
12	FLAME 16K
13	FLAME 15K
14	FLAME 14K
15	FLAME 13K
16	FLAME 12K
17	FLAME 11K
18	FLAME 10K
19	FLAME 9K
20	FLAME 8K
21	FLAME 7K
22	FLAME 6K
23	FLAME 5K
24	FLAME 4K
25	FLAME 3K
26	FLAME 2K
27	FLAME 1K
28	DUST 1 LEFT
29	DUST 2
30	DUST 3
31	DUST 4 RIGHT
32	*BRITE LEFT FLASH (TOP BOX)
33	*BRITE RIGHT SLINGSHOT
34	*BRITE SWORD
35	*BRITE DRAGON 3 (TOP BOX)
36	*BRITE MILLION
37	*BRITE SHIELD
38	*BRITE MIDDLE SKILL
39	*BRITE DROP TARGETS
40	LEFT RETURN
41	RIGHT RETURN
42	FLAME 2X
43	FLAME 3X
44	RESTORE SWORD BOTTOM
45	RESTORE SWORD TOP
46	ADVANCE LEVEL BOTTOM
47	ADVANCE LEVEL TOP
48	RESTORE DUST BOTTOM
49	RESTORE DUST TOP
50	TELEPORT RIGHT BOTTOM
51	TELEPORT RIGHT TOP
52	RESTORE SHIELD BOTTOM
53	RESTORE SHIELD TOP
54	TELEPORT LEFT BOTTOM
55	TELEPORT LEFT TOP
56	DUNGEON LEVEL 2
57	DUNGEON LEVEL 3
58	DUNGEON LEVEL 4
59	DUNGEON LEVEL 5
60	BUMPER TOP
61	BUMPER LEFT
62	BUMPER RIGHT
63	BUMPER BOTTOM
64	DRAGONS LAIR LEFT
65	DRAGONS LAIR RIGHT
66	*BRITE LEFT SLINGSHOT
67	*BRITE RIGHT FLASH (TOP BOX)
68	*BRITE DRAGON 1 (TOP BOX)
69	*BRITE DRAGON 2 (TOP BOX)
70	*BRITE DUST
71	*BRITE TOP SKILL
72	*BRITE EXTRA BALL @ (EXTRA LIFE)
73	*BRITE BOTTOM SKILL
74	SKILL HELP LEFT
75	SKILL HELP RIGHT
76	RESTORE WEAPONS

* = BRITE LITE LOCATIONS

@ = SHOOT-AGAIN

GENERAL ILLUMINATION LITES IDENTIFICATION

NOTE: THERE ARE 27 LOCATIONS IDENTIFIED BY A "SHADED CIRCLE" ON ILLUSTRATION IIb.

IX. ROUTINE MAINTENANCE ON LOCATION:

After successful completion of the Self Diagnostic Test Procedure, set the game up for play. Exercise each roll-over, thumper bumper, slingshot, etc., with a game ball until each switch assembly on the Playfield has been checked for proper operation. If actuating a switch assembly results in intermittent or no response, clean contacts by gently closing them on a clean business card or piece of paper and wiping until the contacts are wiped clean. Re-gap, if necessary to 1/16". Do not burnish or file gold plated switch contacts.

X. SWITCH ASSEMBLY ADJUSTMENTS:

GENERAL:

All switch assemblies consist of leaf springs, contacts, separators, plastic tubing and screws to hold them to the mounting surface. Before attempting to adjust a switch assembly, make sure that these screws are tight. If not, tighten screw closest to the contact end of the leaf spring first. This will prevent the assembly from being secured in such a manner that the leaf springs tend to fan out. In general, all leaf springs are adjusted for a 1/16" gap between contacts in the open position and .010" over-travel or wipe in the closed position. All contacts should be free of dust and dirt. Contacts, with the exception of the flipper button switch assemblies, are plated to resist corrosion. Filing or burnishing breaks the finish and encourages corrosion. Clean contacts by gently closing them on a clean business card or piece of paper and wiping until the contacts are wiped clean.

For the flipper button switch assemblies **ONLY:** Tarnish can be removed with a contact file followed by a burnishing tool. Severely pitted contacts must be placed and adjusted only when they are found to be a source of game malfunction.

XI. SERVICE HINTS:

The Bally Playfield has an improved tuff-coat finish with excellent wearing properties. Life expectancy of the Playfield as well as play appeal, can be extended by periodic cleaning.

DO: Bally recommends you clean your Playfield with Wildcat #125 (Wildcat Chemical Co., 1349 East Seminary Drive, Fort Worth, Texas 76115; Phone 1-817-924-8321). Wildcat #125 is a combination cleaner and polish. Bally has tried and tested this product and found it to be very effective. If Wildcat #125 is not available, Bally suggests you ask your distributor to order it. Inspect and hand polish the ball in a clean cloth. A chipped ball must be replaced. It can ruin the finish on the playfield in a short period of time.

DON'T: Use water in large quantities, highly caustic cleaners, abrasive cleaners and cleaning pads on the playfield, or allow a wax or polish build up. Waxes yellow with age and spoil appeal.

XII OH06 DUNGEONS & DRAGONS

PANEL TOP PARTS

- | | |
|--|-----------------|
| 1. FLIPPER ASSEMBLY SINGLE SWITCH RIGHT | AC70-00022-0100 |
| 2. FLIPPER ASSEMBLY SINGLE SWITCH LEFT | AC70-00022-0200 |
| 3. FLIPPER ASSEMBLY DOUBLE SWITCH RIGHT | AC70-00023-0100 |
| 4. THUMPER BUMPER ASSEMBLY | A967-00053-0100 |
| 5. SLINGSHOT KICKER ASSEMBLY LEFT & RIGHT | A967-00059-0000 |
| 6. BALL SAVER ASSEMBLY LEFT | AE94-00040-0000 |
| 7. BALL SAVER ASSEMBLY RIGHT | AE94-00041-0000 |
| 8. MULTI-BALL KICKER ASSEMBLY | AH01-00027-0000 |
| 9. BACKBOARD ASSEMBLY | AH06-00009-0000 |
| 10. TOP PLATFORM ASSEMBLY | AH06-00024-0000 |
| 11. DROP TARGET ASSEMBLY 3 IN-LINE | AH06-00042-0000 |
| 12. TELEPORT DROP TARGET ASSEMBLY | A365-00374-0100 |
| 13. KNOCKER ASSEMBLY 2-LUG LEFT | AH06-00045-0000 |
| 14. TOP MOUNTED KICKER ASSEMBLY | A360-00234-0000 |
| 15. KNOCKER ASSEMBLY 2-LUG RIGHT | A360-00235-0000 |
| 16. TARGET, SWITCH, BRACKET, DIODE, & CAP: YELLOW; LUG RIGHT | A365-R0306-F113 |
| 17. TARGET, SWITCH, BRACKET, DIODE, & CAP: RED; LUG RIGHT | A365-R0307-F111 |
| 18. TARGET, SWITCH, BRACKET, DIODE, & CAP: BLUE; LUG RIGHT | A365-R0307-F112 |
| 19. SHAFT W/ARM & STUD ASSEMBLY: RIGHT | A365-00321-0100 |
| 20. SHAFT W/ARM & STUD ASSEMBLY: LEFT | A365-00321-0200 |
| 21. OPTICAL MULTI-BALL TROUGH ASSEMBLY | A365-00347-0100 |
| 22. TELEPORT DROP TARGET ASSEMBLY | A365-00374-0100 |
| 23. GATE, BRACKET & WIRE FORM ASSEMBLY | AA40-00034-0000 |
| 24. GATE, BRACKET & WIRE FORM ASSEMBLY | A360-00214-0000 |
| 25. GATE, BRACKET & WIRE FORM ASSEMBLY | AH06-00025-0000 |
| 26. WIRE-TO-MOUNTING BRACKET ASSEMBLY | AH06-00021-0000 |
| 27. BRACKET W/WIRE FORM ASSEMBLY: ROLLOVER LEFT | A331-00042-0000 |
| 28. BRACKET W/WIRE FORM ASSEMBLY: ROLLOVER LEFT | A360-00217-0000 |
| 29. SWITCH ASSEMBLY: ROLLOVER W/DIODE & CAP | A020-00095-0111 |
| 30. SWITCH ASSEMBLY: GATE W/DIODE & CAP | A020-00094-0111 |
| 31. SWITCH W/BRACKET & PLATE ASSEMBLY: SLINGSHOT | A360-00230-0000 |
| 32. SWITCH/BRACKET & DIODE ASSEMBLY: REBOUND | A360-00239-0000 |
| 33. SWITCH W/DIODE & CAP ASSEMBLY | A360-00603-0002 |
| 34. SWITCH W/DIODE & PLATE ASSEMBLY | A365-00034-0000 |
| 35. SWITCH W/DIODE & PLATE ASSEMBLY | A365-00035-0000 |
| 36. LIGHT DOME: PLASTIC, BLUE | 0017-00042-0742 |
| 37. LIGHT DOME: PLASTIC, CLEAR | 0017-00042-0745 |
| 38. WIRE FORM: LEFT BALL CAPTURE | OH06-00905-0000 |
| 39. WIRE FORM RAMP UNIT: RIGHT | OH06-00910-00XF |
| 40. WIRE FORM RAMP UNIT: LEFT | OH06-00911-00XF |
| 41. WIRE FORM: INSIDE DRAIN RIGHT | OH06-00913-0100 |
| 42. WIRE FORM: INSIDE DRAIN LEFT | OH06-00913-0200 |
| 43. WIRE FORM: BALL GUIDE | 0360-00175-5300 |
| 44. WIRE FORM: BALL GUIDE | 0365-00151-2000 |
| 45. PLATE: LEFT RAMP ENTRANCE | OH06-00134-0000 |
| 46. CAP: THUMPER BUMPER, AMBER | 0017-00042-0520 |
| 47. COLLAR: THUMPER BUMPER, RED | 0017-00042-0566 |
| 48. SHOOTER GAUGE | OH06-00100-00XF |
| 49. BOTTOM ARCH | OH06-00921-0000 |
| 50. BOTTOM ARCH EXTENSION | 0370-00918-1000 |
| 51. LEFT RAMP ENTRANCE ASSEMBLY | AH06-00048-0000 |
| 52. SCOOP: LEFT BALL CAPTURE | OH06-00104-0000 |
| 53. RIGHT BALL CATCH ASSEMBLY | AH06-00029-0000 |




FIGURE II c

XIII **OH06 DUNGEONS & DRAGONS**





FIGURE II d

RAMP PARTS

- | | | |
|----|---|-----------------|
| 1. | PLATE-TO-CIRCLE RAMP ASSEMBLY | AH06-00028-0000 |
| 2. | STRAIGHT RAMP PIVOT ASSEMBLY | AH06-00022-0000 |
| 3. | PLATES-TO-STRAIGHT RAMP ASSEMBLY | AH06-00023-0000 |
| 4. | WOOD RAMP ASSEMBLY | AH06-00027-0000 |
| 5. | THUMPER BUMPER EXIT, RAMP
ENTRANCE ASSEMBLY: RIGHT | AH06-00050-0000 |

RUBBER RINGS

- | | | |
|----|----------------|-----------------|
| A. | RING | 0017-00041-0633 |
| B. | RING: 5/16" | 0017-00041-0637 |
| C. | RING: .23" | 0017-00041-0641 |
| D. | RING: 3/4" | 0017-00041-0642 |
| E. | RING: 1" | 0017-00041-0643 |
| F. | RING: 1-1/2" | 0017-00041-0644 |
| G. | RING: 2-1/2" | 0017-00041-0646 |
| J. | RING: 3" (RED) | 0017-00041-0682 |

POST

- | | | |
|----|---|-----------------|
| K. | POST: (BLUE) PLASTIC 1" | 0017-00042-0586 |
| L. | POST: (BLUE) PLASTIC 1-3/16" | 0017-00042-0584 |
| M. | POST: METAL-MINI
(W/THREADS FOR 10/32 NUT) | 0365-00700-00XF |
| N. | POST: 3/8" x 1-3/16" | 0365-00980-0000 |

RUBBER BUMPER USE

- | | |
|------------------------------|-----------------|
| M.-POST: METAL-MINI | 0017-00041-0633 |
| K. & L.-POST: (BLUE) PLASTIC | 0017-00041-0637 |




FIGURE III. DUNGEONS AND DRAGONS PINBALL GAME

XIV. DUNGEONS & DRAGONS FEATURE OPERATION & SCORING

1. SHOOTER LANE SKILL SHOT FEATURE

When a ball is delivered to the plunger in the shooter lane, a flashing "100 K" light at the left end of the backboard will turn on. The shooter lane SKILL SHOT, which awards 100,000 points, can be made as follows:

1. Shoot the ball with the plunger into the upper left inclined lane.
2. The ball must pass thru the backboard entrance gate (located under the "100 K" light) which makes a switch.
3. The ball must then roll back down the inclined lane.

However, if the ball continues to roll thru a circular plastic ramp (hidden behind the backboard) and then passes thru a backboard exit gate (which breaks a switch), the 100,000 points will not be awarded.

The inclined lane has two rollover switches. Making each rollover switch awards 5,000 points. Making the backboard entrance gate switch awards 5,000 points.

If the SKILL SHOT off the plunger is unsuccessful, the "100 K" light will continue to flash until points are scored anywhere on the playfield. At that time, the "100 K" light turns off.

2. DUNGEON LEVEL FEATURE

The DUNGEON LEVEL (playfield multiplier) value can be increased by hitting the ball with the upper right Flipper as follows:

1. The ball rolls up the left inclined lane making two (2) rollover switches.
2. The ball makes the backboard entrance gate switch (located under the "100 K" light).
3. The ball passes thru the circular plastic ramp which is hidden behind the backboard.
4. The ball breaks the backboard exit gate switch with the ball rolling back to the playfield via the left DRAGON'S LAIR wire ramp.

Each time the above ramp shot is made, the playfield multiplier values and game points are awarded as follows:

FIGURE 1. DUNGEON LEVELS: COMPLETIONS & AWARDS

DUNGEON LEVEL RAMP COMPLETION	DUNGEON LEVEL LIGHT LIT	PLAYFIELD MULTIPLIER VALUE AWARD	ROLLOVER SWITCHES AWARD	BACKBOARD GATE SWITCHES AWARD	TIME ALLOWED FOR RAMP COMPLETIONS*
1st time	2X	2X	10,000 points	10,000 points	20 seconds
2nd time	3X	3X	10,000 points	10,000 points	20 seconds
3rd time	4X	4X	10,000 points	10,000 points	20 seconds
4th time	5X	5X	10,000 points	10,000 points	20 seconds

*Adjustable—°See REGISTER "DUNGEON TIMER" for adjustment times below.

NOTES:

1. If successive DUNGEON LEVEL ramp completions fall behind the set time limit, the playfield multiplier value will decrease in steps.
2. Making each rollover switch in the left inclined lane awards 5,000 points.
3. Making the backboard entrance gate switch awards 5,000 points.
4. Breaking the backboard exit gate switch awards 5,000 points.
5. The maximum DUNGEON LEVEL (playfield multiplier) value awarded is 5X.
6. Each time the DUNGEON LEVEL ramp is completed (the first four times), the DUNGEON LEVEL (playfield multiplier) value appears on the display.

°The time allowed to advance the DUNGEON LEVEL to the next higher value, before it reverts to the next lower value, is adjustable using one of the following settings:

REGISTER	SETTING	FUNCTION
DUNGEON TIMER	0	10 Seconds To Advance DUNGEON LEVEL
DUNGEON TIMER	1	20 Seconds To Advance DUNGEON LEVEL
DUNGEON TIMER	2	40 Seconds To Advance DUNGEON LEVEL
DUNGEON TIMER	3	60 Seconds To Advance DUNGEON LEVEL

3. DRAGON'S FLAME BONUS FEATURE

The DRAGON'S FLAME consists of twenty (20) diamond-shaped lights "1K" thru "20K" with respective bonus point values of 1,000 points thru 20,000 points. Each successive DRAGON'S FLAME "portion" is "extinguished" (each light turns off) by hitting a lit target in any of the three (3) Weapon Target groups. Weapon Target descriptions and points awarded are shown in Figure 2.

FIGURE 2. WEAPON TARGETS: DESCRIPTIONS & POINTS AWARDED

WEAPON EXTINGUISHES FLAME	WEAPON TARGET COLOR	NUMBER OF TARGETS	AWARD PER WEAPON TARGET HIT	
			LIT*	UNLIT
DUST	Yellow	4	5,000 points	3,000 points
SHIELD	Blue	3	5,000 points	3,000 points
SWORD	Red	3	5,000 points	3,000 points

*An extra 5,000 points is awarded when all of the lit targets are hit in any Weapon Target group.

When all of the targets are unlit in any one of the three (3) Weapon Target groups, the RESTORE ALL WEAPONS light, located on the right side of the bottom thumper bumper, turns on. Making the rollover switch in the RESTORE ALL WEAPONS lane, located below the right DRAGON'S LAIR wire ramp, will re-light all unlit Weapon Targets.

When all of the DUST targets are completed (all are unlit), the "RESTORE DUST" light in front of the right TELEPORT lane flashes on. All unlit DUST targets are re-lit by:

1. Having the ball enter the right TELEPORT lane while the right "TELEPORT" light is flashing. See "TELEPORT FEATURE" on page 1-20.
2. Hitting the first, second or third BELL TOWER in-line drop target or by making its rear gate switch. See "BELL TOWER FEATURE" on page 1-18.

When all of the SHIELD targets are completed (all are unlit), the "RESTORE SHIELD" light in front of the left TELEPORT flashes on. Entering the left TELEPORT lane will re-light all of the unlit SHIELD targets. See "TELEPORT FEATURE" on page 1-20.

When all of the SWORD targets are completed (all are unlit), the "RESTORE SWORD" light in front of the upper left inclined lane flashes on. Having the ball enter the inclined lane and make the first of two (2) rollover switches will re-light all of the unlit SWORD targets.

By hitting the Weapon Targets, the DRAGON'S FLAME can be repeatedly extinguished until regular game points, instead of bonus points, are earned. Each time all twenty (20) DRAGON'S FLAME lights are turned off, the DRAGON'S FLAME is completely extinguished. This ends the first completion round. All twenty (20) lights will then immediately re-light. At the same time, the "2X FLAME" light turns on which tells the player to begin the second DRAGON'S FLAME completion round. Figure 3 shows the completion round sequence.

FIGURE 3. DRAGON'S FLAME COMPLETION ROUND SEQUENCE

DRAGON'S FLAME COMPLETELY EXTINGUISHED	NEXT FLAME COMPLETION ROUND IN PROGRESS	
	"2X FLAME" LIGHT	"3X FLAME" LIGHT
	Off	Off
1st time	On	Off
2nd time	Off	On
3rd time	Off	On
4th time	On	On
5th time	On	On

All of the DRAGON'S FLAME lights will re-light after every completion throughout the rest of the game.

For every DRAGON'S FLAME light turned off, its bonus point value accumulates until after the fifth completion and is awarded when:

1. The left DRAGON'S LAIR or the right DRAGON'S LAIR (see the DRAGON'S LAIR FEATURE on page 1-20) is entered, whether either DRAGON'S LAIR is lit or unlit.
2. The ball drains thru the outhole.

However, after the fifth completion of the DRAGON'S FLAME, the FLAME value points will accumulate **only** as regular game points and will be awarded each time immediately upon completion of all twenty (20) DRAGON'S FLAME lights.

°The DUST targets, SHIELD targets and SWORD targets can be cleared or saved at the end of each ball using one of the following settings:

<u>REGISTER</u>	<u>SETTING</u>	<u>FUNCTION</u>
RECALL TARGETS	0	No, do not recall all Weapon Targets from ball to ball.
RECALL TARGETS	1	Yes, recall all Weapon Targets from ball to ball.

4. BELL TOWER FEATURE & EXTRA LIFE FEATURE

The BELL TOWER can be entered only when its movable ramp is in a lowered position. This happens only after the right Teleport Drop Target captures a ball. See the "TELEPORT FEATURE" on page 1-20.

Before the ball passes thru the rear gate which makes a switch, three (3) in-line drop targets must be hit in succession. Points and an EXTRA BALL are awarded as shown in Figure 4:

FIGURE 4. BELL TOWER AWARD SEQUENCE

BELL TOWER	1ST DROP TARGET HIT	2ND DROP TARGET HIT	3RD DROP TARGET HIT	REAR GATE SWITCH MADE
POINTS AWARDED	10,000 points	25,000 points	50,000 points	100,000 points
DURING 1ST BALL			Qualifies EXTRA LIFE & starts X-BALL TIMER	If within time limit, collects EXTRA LIFE*
DURING 2ND BALL		Qualifies EXTRA LIFE & starts X-BALL TIMER	If within time limit, collects EXTRA LIFE*	
DURING 3RD BALL	Qualifies EXTRA LIFE & starts X-BALL TIMER	If within time limit, collects EXTRA LIFE*		

*Adjustable—°See REGISTER "X-BALL TIMER" below.

NOTES:

1. "EXTRA LIFE" = EXTRA BALL
2. The "EXTRA LIFE" qualify light is located at the right end of the backboard.
3. The "EXTRA LIFE" collect light is located above the outhole.
4. If an EXTRA LIFE is earned at one ball level, the **same** EXTRA LIFE scoring requirements are repeated at the next higher ball level.

Passing the ball thru the BELL TOWER rear gate qualifies the MILLION SHOT. See the "MILLION SHOT FEATURE" below.

°The length of time given to collect EXTRA LIFE is adjustable by using one of the following settings:

<u>REGISTER</u>	<u>SETTING</u>	<u>FUNCTION</u>
X-BALL TIMER	0	Length of time is 4 seconds.
X-BALL TIMER	1	Length of time is 6 seconds.
X-BALL TIMER	2	Length of time is 10 seconds.
X-BALL TIMER	3	Length of time is 16 seconds.

5. MILLION SHOT FEATURE

Passing the ball thru the BELL TOWER rear gate qualifies the MILLION SHOT (see the "BELL TOWER FEATURE & EXTRA LIFE FEATURE" above). This activates a flashing "MILLION" light located at the center of the backboard. A timer is also activated allowing 3 seconds to make the MILLION SHOT. The ball must travel up the upper left inclined lane, thru the pastic ramp located behind the backboard) making the backboard entrance ramp gate switch and also breaking the backboard exit gate switch to collect 1,000,000 points. The MILLION SHOT is re-qualified each time the ball passes thru the BELL TOWER rear gate.

6. MAGIC SAVE FEATURE & AUTO SAVER FEATURE

Two "MAGIC-SAVE" (flex-save) lanes are in this game. Two rollover buttons are in each one of these combination return/out lanes. Each lane contains a flexible spring steel ball guide which can be moved to a closed position by a Ball Saver gate. This occurs when the lamps are lit under the rollover buttons. The left Ball Saver gate is manually activated with a push-button located under the left Flipper push-button on the Cabinet. The right Ball Saver gate is manually activated with a push-button located under the right Flipper push-button. When either Ball Saver gate is manually activated, its respective lane changes from being an "outlane" to a "return lane" for a fixed length of time (adjustable—°see REGISTER "GATE ON TIMER" and REGISTER "CONTROL GATE TIMER") after which it returns to being an "outlane."

Whenever the two rollover button lights are flashing in either Ball Saver lane and the ball passes over both buttons, the AUTO SAVER feature automatically activates the Ball Saver gate to close the lane's flexible ball guide, for a fixed length of time, returning the ball to the Flipper.

At the start of each ball, the °AUTO SAVER feature remains active (two flashing rollover button lights in each Ball Saver lane) until the game score is greater than 200,000 points (adjustable—°see REGISTER "AUTO SAVER" below). The AUTO SAVER feature is then disabled for both Ball Saver lanes but the player can still earn one AUTO-SAVE per lane at a time. Completing all three (3) lit SHIELD targets activates the left MAGIC-SAVE lane's AUTO-SAVE. Completing all four (4) lit DUST targets activates the right MAGIC-SAVE lane's AUTO-SAVE. The player can retain either MAGIC-SAVE lane's AUTO-SAVE by manually activating the Ball Saver gate before the AUTO-SAVE is used.

Completing either MAGIC-SAVE lane, with its rollover button lights flashing, awards 10,000 points. Completing either Ball Saver lane, with its rollover button lights unlit, awards 5,000 points.

°The level of game points, beyond which the AUTO SAVER feature is disabled, is adjustable by using one of the following settings:

REGISTER	SETTING	FUNCTION
AUTO SAVER	0	Game point level is no points.
AUTO SAVER	1	Game point level is 100,000 points.
AUTO SAVER	2	Game point level is 200,000 points.
AUTO SAVER	3	Game point level is 300,000 points.

°The initial length of time (for each player) either Ball Saver gate remains closed after being manually activated is adjustable by using one of the following settings. During the game, this time length is also controlled by the "CONTROL GATE TIMER" REGISTER. See note below.

REGISTER	SETTING	FUNCTION
GATE ON TIMER	0	Length of time is 0.83 second.
GATE ON TIMER	1	Length of time is 1.00 second.
GATE ON TIMER	2	Length of time is 1.16 seconds.
GATE ON TIMER	3	Length of time is 1.33 seconds.
GATE ON TIMER	4	Length of time is 1.50 seconds.
GATE ON TIMER	5	Length of time is 1.66 seconds.
GATE ON TIMER	6	Length of time is 1.83 seconds.
GATE ON TIMER	7	Length of time is 2.00 seconds.

°REGISTER "CONTROL GATE TIMER," for each player, controls the length of time (along with the "GATE ON TIMER" REGISTER) either Ball Saver gate remains closed after being manually activated. See note below.

REGISTER	SETTING	FUNCTION
CONTROL GATE TIMER	0	Ball Saver is manually activated 6 times.
CONTROL GATE TIMER	1	Ball Saver is manually activated 8 times.
CONTROL GATE TIMER	2	Ball Saver is manually activated 10 times.
CONTROL GATE TIMER	3	Ball Saver is manually activated 12 times.
CONTROL GATE TIMER	4	Ball Saver is manually activated 14 times.
CONTROL GATE TIMER	5	Ball Saver is manually activated 16 times.
CONTROL GATE TIMER	6	Ball Saver is manually activated 18 times.
CONTROL GATE TIMER	7	Ball Saver is manually activated 20 times.

NOTE: The Gate On Timer is initialized for each player at the beginning of the game. See REGISTER "GATE ON TIMER"). The game counts the number of times the Ball Saver gates are manually activated by a particular player. If a match is found when compared to the number of times allowed, as set in the "CONTROL GATE TIMER" REGISTER, the next lower time setting in the "CONTROL GATE TIMER" REGISTER is selected automatically.

7. DRAGON'S LAIR FEATURE

This game has two DRAGON'S LAIR lane and wire ramp combinations. One is located on the upper left side of the Playfield and the other is located on the upper right side. When a ball enters into either DRAGON'S LAIR lane, it rolls down against a Ball Kicker (Knocker) and also makes a rollover switch. This activates the Ball Kicker's solenoid so that its plunger kicks the ball up the DRAGON'S LAIR lane, around and thru the wire ramp back onto the Playfield.

A ball captured in the left TELEPORT lane flashes the left DRAGON'S LAIR light. This qualifies two-ball multi-ball play which begins after the ball enters the left DRAGON'S LAIR. See the "MULTI-BALL PLAY" feature below and on page 1-21. A ball captured in the right TELEPORT lane begins the same sequence involving the right DRAGON'S LAIR and its light.

Completing either DRAGON'S LAIR, regardless of whether its light is lit or unlit, awards 10,000 points and also awards the accumulated points in the DRAGON'S FLAME BONUS. See the "DRAGON'S FLAME BONUS" feature on page 1-17.

8. TELEPORT FEATURE

The left and right TELEPORT lanes each contain a Teleport Drop Target assembly. When either one of the Teleport Drop Targets captures a ball:

1. It is lowered (with the trapped ball) below the Playfield surface so that the flat top of the Teleport Drop Target is even with the top surface of the Playfield.
2. Its "TELEPORT" light starts flashing.
3. A new ball is fed into the shooter lane.
4. A "SUMMON HELP" light starts flashing on the Backboard which qualifies two-ball multi-ball play.

NOTE: When balls are captured in both Teleport Drop Targets, two-ball multi-ball play is qualified. See "MULTI-BALL PLAY" feature below and on page 1-21. For two-ball multi-ball play, one captured ball is released. For three-ball multi-ball play, captured balls in each of the two Teleport Drop Targets are released.

After the left Teleport Drop Target is lowered, the ball passes thru the left TELEPORT lane without interruption. Lowering the right Teleport Drop Target lowers the BELL TOWER'S movable ramp which provides access to the BELL TOWER. See the BELL TOWER feature on page 1-18.

*When the game is over, the selected setting in the "RETAIN BALLS" REGISTER determines whether Teleport Drop Targets retain or eject captured balls.

<u>REGISTER</u>	<u>SETTING</u>	<u>FUNCTION</u>
RETAIN BALLS	0	One or both Teleport Drop Targets will eject held ball at end of game.
RETAIN BALLS	1	One Teleport Drop Target retains ball & other Teleport Drop Target ejects ball at end of game.
RETAIN BALLS	2	Both Teleport Drop Targets retain held balls at end of game.

9. MULTI-BALL PLAY FEATURE

Two-ball multi-ball play is achieved using the left DRAGON'S LAIR as follows: See the "DRAGON'S LAIR FEATURE" above.

1. When a ball is captured by the Teleport Drop Target in the left TELEPORT lane, the left "DRAGON'S LAIR" light and the "SUMMON HELP" light both flash on. See the "TELEPORT FEATURE" above. This qualifies two-ball multi-ball play.
2. After a new ball enters the left DRAGON'S LAIR, the captured ball is ejected from the Teleport Drop Target. Two-ball multi-ball play now begins.

Two-ball multi-ball play is achieved using the right DRAGON'S LAIR as follows: See the "DRAGON'S LAIR FEATURE" above.

1. When a ball is captured by the Teleport Drop Target in the right TELEPORT lane, the right "DRAGON'S LAIR" light and the "SUMMON HELP" light both flash on. See the "TELEPORT FEATURE" above. This qualifies two-ball multi-ball play.
2. After a new ball enters the left DRAGON'S LAIR, the captured ball is ejected from the Teleport Drop Target. Two-ball multi-ball play now begins.

Two-ball or three-ball multi-ball play is achieved using the DUNGEON LEVEL inclined lane and circular ramp combination as follows: See the "DUNGEON LEVEL FEATURE" on page 1-16.

For two-ball multi-ball play:

1. A ball captured by the Teleport Drop Target in either TELEPORT lane flashes the "SUMMON HELP" light. This qualifies two-ball multi-ball play.
2. After the ball completes the DUNGEON LEVEL inclined lane and circular ramp combination, the captured ball is ejected from the Teleport Drop Target. Two-ball multi-ball play now begins.

Three-ball multi-ball play is achieved the same way as two-ball except that both Teleport Drop Targets must capture a ball.

Achieving successive multi-ball plays becomes increasingly difficult due to an increase in the number of required Teleport Drop Target ball captures as shown in Figure 5 on page 1-21.

FIGURE 5. THREE-BALL MULTI-BALL PLAY QUALIFICATION SEQUENCE

3-BALL MULTI-BALL PLAY QUALIFICATION	REQUIRED TELEPORT DROP TARGET ACTIONS
1st time	Both Teleport Drop Targets capture game balls.
2nd time	1. Ball is captured by Teleport Drop Target "A". 2. Ball is captured by Teleport Drop Target "B". 3. Ball is ejected from Teleport Drop Target "A". 4. Ball is captured by Teleport Drop Target "A".
3rd time	The above steps 1 thru 4 are repeated & followed by: 5. Ball is ejected from Teleport Drop Target "B". 6. Ball is captured by Teleport Drop Target "B".
4th time	The above steps 1 thru 6 are repeated & followed by: 7. Ball is ejected from Teleport Drop Target "A". 8. Ball is captured by Teleport Drop Target "A".
5th time	The above steps 1 thru 8 are repeated & followed by: 9. Ball is ejected from Teleport Drop Target "B". 10. Ball is captured by Teleport Drop Target "B".

The 6th, 7th, 8th, 9th times and beyond, add on additional steps as shown above.

NOTES:

1. Teleport Drop Target "A" or Teleport Drop Target "B" could be in the left TELEPORT lane or the right TELEPORT lane. Teleport Drop Target "A" is the FIRST Teleport Drop Target to capture a game ball. Teleport Drop Target "B" is the SECOND Teleport Drop Target to capture a game ball.
2. Two-ball multi-ball play can interrupt any of the above Teleport Drop Target action sequences before three-ball multi-ball is qualified or achieved. However, the required Teleport Drop Target action sequence continues.
3. Whenever the "100 K" light flashes on, the "SUMMON HELP" light (if already flashing) turns off. This prevents achieving multi-ball play resulting from an unsuccessful shooter lane SKILL SHOT attempt.

*The selected setting in the "MULTI-BALL SAVERS" REGISTER controls whether the AUTO-SAVER feature, during multi-ball play, is active or inactive:

REGISTER	SETTING	FUNCTION
MULTI-BALL SAVERS	0	Does not activate AUTO-SAVER during multi-ball play.
MULTI-BALL SAVERS	1	Activates AUTO-SAVER during multi-ball play.

10. MISCELLANEOUS FEATURES

The SPECIAL is awarded when the game score reaches the first threshold of 1,750,000 points.

Each rebound awards 10 points.

Each slingshot awards 10 points.

Each thumper bumper awards 100 points.

°The selected setting in the "ATTRACT SOUND" REGISTER enables or disables, after the game is over, the ATTRACT SOUND mode while displaying Hi-score or Instructions.

<u>REGISTER</u>	<u>SETTING</u>	<u>FUNCTION</u>
ATTRACT SOUND	0	Disables the ATTRACT SOUND mode.
ATTRACT SOUND	1	Enables the ATTRACT SOUND mode.

In Basic Options:

°The selected setting in the "SLINGSHOT" REGISTER controls whether the slingshots are active or inactive.



<u>REGISTER</u>	<u>SETTING</u>	<u>FUNCTION</u>
SLINGSHOT	0	De-activates the slingshots.
SLINGSHOT	1	Activates the slingshots.

°The number of tilt warnings is adjustable by using one of the following settings:

<u>REGISTER</u>	<u>SETTING</u>	<u>FUNCTION</u>
TILT WARNING	0	No tilt warning
TILT WARNING	1	One tilt warning
TILT WARNING	2	Two tilt warnings
TILT WARNING	3	Three tilt warnings

SECTION 2
**Component Layouts,
Schematics & Wiring Diagrams**

J3-15 — 13
 J3-4 — 27
 J3-6 — 97
 J2-1 — 80
 VOLUME
 L HIPER 50
 J3-14 — 14
 J3-4 — 27
 J7-7 — 28
 J7-8 — 10
 PER
 T BUTTON
 J2-5 — 70



COLOR CODE


1=RED
 2=BLUE
 3=YELLOW
 4=GREEN
 5=WHITE
 6=BROWN
 7=ORANGE
 8=BLACK
 9=GRAY
 0=NO TRACE
 11-VIOLET

NOTES:
 W. STONE
 10/5/87

BALLY MIDWAY MFG. CO.




DUNGEONS AND DRAGONS
 CABINET DIAGRAM
 M051-00H06-A003

SHEET 1 OF 1 REV A








KEYBOARD

PIN	DESIG	COLOR
1		
2		
3	I3	21
4	KEY	
5	ST3	35
6	I2	20
7		
8	ST2	74
9		
10	I1	65
11	ST1	14
12		
13	I0	15
14		
15	ST0	13



* OPTIONAL- NOT USED IN ALL GAMES






COLOR CODE

- 1♦ RED
- 2♦ BLUE
- 3♦ YELLOW
- 4♦ GREEN
- 5♦ WHITE
- 6♦ BROWN
- 7♦ ORANGE
- 8♦ BLACK
- 9♦ GRAY
- 0♦ NO COLOR
- 11♦ VIOLET

SOLENOIDS

NOTES:	BALLY MIDWAY MFG. CO.	
W. STONE	DUNGEONS AND DRAGONS PLAYFIELD DIAGRAM M051-00H06-A005	
10/5/87		
	SHEET 1 OF 3	REV A

05 OCT 87 10:46 / USER/HES/DUNGEON/PLAYFIELD 1. DRAW



TO J5 PIN 3 — BLK

KEY — 2

TO J5 PIN 1 — RED

1 GND

2

A084-91895-B000

4 POS. EMITTER PCB

3 N/U

4 5V

OPTIC BALL SENSOR BD.

TO J4 PIN 1 — WHT-VIO

TO J4 PIN 4 — BRN

TO J4 PIN 3 — ORN

TO J4 PIN 2 — BLK

1 STROBE

2 N/U

3 TROUGH 1 (LEFT)

A084-91894-B000

4POS. DETECTOR PCB

KEY — 4

5 TROUGH 2 (MIDDLE)

6 TROUGH 3 (RIGHT)

COLOR CODE

1-RED	6-BROWN
2-BLUE	7-ORANGE
3-YELLOW	8-BLACK
4-GREEN	9-GRAY
5-WHITE	0-NO TRACE
	11-VIOLET

NOTE 1. ALL SWITCH DIODES ARE 1N4148

NOTE 2. * INDICATES NOT USED ON PLAYFIELD. DRAWING ONLY TO SHOW RESPECTIVE CABINET SWITCH POSITION IN SWITCH MATRIX.

NOTE 3. ALL CAPACITORS ARE .05MF, 25V

PLAYFIELD SWITCHES

NOTES:

W. STONE


10/5/87


BALLY MIDWAY MFG. CO.

DUNGEONS AND DRAGONS
PLAYFIELD DIAGRAM
M051-00H06-A005

SHEET 2 OF 3

REV A





NOTE: # = LOCATED IN TOP BOX (PART OF BACKBOX)

COLOR CODE

1♦ RED	6♦ BROWN
2♦ BLUE	7♦ ORANGE
3♦ YELLOW	8♦ BLACK
4♦ GREEN	9♦ GRAY
5♦ WHITE	0♦ NO COLOR
	11♦ VIOLET


NOTE: DIODES ARE 1N4004

ALL FUSES IN FUSEBOARD ARE
3/4A MDQ/250V AND LOCATED
IN THE BACKBOX

FEATURE LIGHTS AND BRIGHT LIGHTS

NOTES:	BALLY MIDWAY MFG. CO.
W. STONE	DUNGEONS AND DRAGONS
10/5/87	PLAYFIELD DIAGRAM
	M051-00H06-A005
	SHEET 3 OF 3
	REV A

85 OCT 97 11:05 USER/HES/DRAGON/PLAYFIELD 3.DRAW



TO
POWER MODULE
J5


BLK-RED 1 PHASE C
FOR PLAYFIELD AND
BACKBOX BRIGHT LIGHTS
BLK-BLU 2 PHASE D
GRN-YEL 1 TO POWER MODULE (PJ6-1)

N/U
0A FEATURE LITES
N/U
N/U
N/U
SOL. BUSS+43V. D. C.
N/U
GEN. ILL. BUS *
N/U
GEN. ILL. BUS *
0B FEATURE LITES

TO PLAYFIELD
* = 32 GI LAMPS

TABLE "A"	
115VAC	2-8, 3-6, 7-10
120VAC	2-8, 4-6, 7-11
220VAC	4-8, 7-9
240VAC	4-8, 7-11



COLOR CODE	
1-RED	6-BROWN
2-BLUE	7-ORANGE
3-YELLOW	8-BLACK
4-GREEN	9-GRAY
5-WHITE	0-NO TRACE
	11-VIOLET



POWER DISTRIBUTION

NOTES:	BALLY MIDWAY MFG. CO.
W. STONE	DUNGEONS AND DRAGONS
10/5/87	BACKBOX
	M051-00H06-A006
	SHEET 1 OF 3
	REV A


87 OCT 87 101157 USER/HES/DRAGON/BACKBOX 1. DRAM




SHOWN JUMPED FOR 115V

NOTE: SEE TABLE "A" FOR
JUMPER OPTIONS.


NOTE: PJ1-PJ4 ARE PART OF
POWER MODULE.



WITHIN BACKBOX
(SHEET 3 OF 3)



TO CABINET



TO CONTROLLER (IN BACKBOX)
(SHEET 2 OF 3)

BACKBOX (SHEET 1 OF 3)

CJ-10		"A"PHASE	"B"PHASE
12	1	◆ SHIELD (LEFT)	◆ RESTORE SWORD (BOT)
13	2	◆ SWORD (LEFT)	◆ ADVANCE LEVEL (TOP)
14	3	◆	◆ TELE RIGHT (BOTTOM)
15	4	◆ FLAME 19K	◆ RESTORE SHIELD (TOP)
18	5	◆ FLAME 16K	◆ LEVEL 2
21	6	◆ FLAME 13K	◆ LEVEL 5
24	7	◆ SHIELD (MIDDLE)	◆ RESTORE SWORD (TOP)
25	8	◆ SWORD (MIDDLE)	◆ RESTORE DUST (BOT)
26	9	◆ EXTRA LIFE	◆ TELE RIGHT (TOP)
28	10	◆ FLAME 12K	◆ TOP BUMPER
31	11	◆ FLAME 18K	◆ TELE LEFT (BOTTOM)
32	12	◆ FLAME 15K	◆ LEVEL 3
36	13	◆ FLAME 11K	◆ LEFT BUMPER
37	14	◆ FLAME 14K	◆ LEVEL 4
	15	◆ KEY	◆
38	16	◆ SHIELD (RIGHT)	◆ ADVANCE LEVEL (BOT)
41	17	◆ SWORD (RIGHT)	◆ RESTORE DUST (TOP)
43	18	◆ FLAME 20K (TOP)	◆ RESTORE SHIELD (BOT)
45	19	◆ FLAME 17K	◆ TELE LEFT (TOP)
CJ-11		"A"PHASE * DENOTES "C" PHASE	"B"PHASE ** DENOTES "D" PHASE
48	1	◆ BRT FLASH LFT	◆ BRT LEFT SLING **
58	2	◆ DUST 2	◆
59	3	◆ FLAME 2K	◆
61	4	◆ FLAME 5K	◆
	5	◆ KEY	◆
62	6	◆ FLAME 8K	◆ DGN LAIR (LEFT)
63	7	◆ DUST 4 (RIGHT)	◆
64	8	◆ FLAME 10K	◆ RIGHT BUMPER
67	9	◆ DUST 1 (LEFT)	◆
68	10	◆ FLAME 3K	◆
71	11	◆ FLAME 6K	◆
72	12	◆ FLAME 7K	◆ DGN LAIR (RIGHT)
73	13	◆ FLAME 4K	◆
74	14	◆ FLAME 1K	◆
75	15	◆ DUST 3	◆
78	16	◆ FLAME 9K	◆ BOTTOM BUMPER

CJ-12		"A"PHASE	"B"PHASE
1	◆	◆	◆
2	◆	◆	◆
3	◆	◆	◆
4	◆	◆	◆
5	◆ KEY	◆	◆
6	◆	◆	◆
7	◆	◆	◆
8	◆	◆	◆
9	◆	◆	◆
10	◆	◆	◆
11	◆	◆	◆
12	◆	◆	◆
13	◆	◆	◆
14	◆	◆	◆
15	◆	◆	◆
16	◆	◆	◆
17	◆	◆	◆

CJ-13		"A"PHASE * DENOTES "C" PHASE	"B"PHASE ** DENOTES "D" PHASE
81	1	◆ BRT R. SLING *	◆ BRT FLASH R. ***
83	2	◆ BRT MILLION *	◆ BRT DUST **
84	3	◆ BRT DT *	◆ BRT B. SKILL **
85	4	◆ FLAME 2X	◆ RESTORE WEAPONS
86	5	◆ BRT M. SKILL *	◆ BRT EXTRA BALL **
87	6	◆ BRT DRAGON 3 ***	◆ BRT DRAGON 2 ***
91	7	◆	◆
93	8	◆ BRT SWORD *	◆ BRT DRAGON 1 ***
	9	◆ KEY	◆
94	10	◆ RIGHT RETURN	◆ SKILL HLP (RIGHT)
95	11	◆ FLAME 3X	◆
96	12	◆ LEFT RETURN	◆ SKILL HLP (LEFT)
97	13	◆ BRT SHIELD *	◆ BRT TOP SKILL **

PLAYFIELD & BACKBOX LAMP OUTPUTS

COLOR CODE

1-RED	6-BROWN
2-BLUE	7-ORANGE
3-YELLOW	8-BLACK
4-GREEN	9-GRAY
5-WHITE	0-NO TRACE
	11-VIOLET

NOTES

CJ-12 NOT USED
 BRIGHT LIGHTS TYPE 912 BULBS (C&D PHASE)
 OTHER LIGHTS TYPE 555 BULBS (A&B PHASE)
 CJ1 THROUGH CJ14 LOCATED ON CONTROLLER BOARD

* = IN TOP BOX

PLAYFIELD INPUTS, BACKBOX INPUTS & OUTPUTS
(SHEET 2 OF 3)

- J-6
- 1 TOP BUMPER
 - 2 LEFT BUMPER
 - 3 RIGHT BUMPER
 - 4 BOTTOM BUMPER
 - 5 DROP TARGET RESET
 - 6 KEY
 - 7 RIGHT FLEXSAVE
 - 8 L. FLIPPER
 - 9 R. FLIPPER

- J-8
- 1
 - 2
 - 3 KEY
 - 4
 - 5
 - 6 SLING RIGHT
 - 7 SLING LEFT

- J-7
- 1
 - 2
 - 3
 - 4
 - 5 KEY
 - 6
 - 7 LEFT FLIPPER SWITCH
 - 8 RIGHT FLIPPER SWITCH

- CABINET SWITCHES
- J-9
- 1 LEFT KICKBACK
 - 2 RIGHT KICKBACK
 - 3 LEFT HIDE A BALL
 - 4 RIGHT HIDE A BALL
 - 5 KEY
 - 6 KICK TO PLAYFIELD
 - 7 RESERVED FOR GERMAN
 - 8 OUTHOLE
 - 9
 - 10 LEFT FLEXSAVE
 - 11 KNOCKER

OUTPUTS TO PLAYFIELD

- CJ-5
- 1
 - 2
 - 3
 - 4
 - 5 KEY
 - 6
 - 7 SJ1-1
 - 8 SJ1-2
 - 9 SJ1-3
 - 10 SJ1-4
 - 11
 - 12
 - 13
 - 14
 - 15 SJ1-8

SOUND INFO. OUTPUT
(SHEET 3 OF 3)

- CJ-4
- 511 1 ST5
 - 80 2 17
 - 70 3 16
 - 60 4 15
 - 5 5 KEY
 - 50 6 14
 - 40 7 13
 - 30 8 12
 - 20 9 11
 - 10 10 10
 - 56 11 ST4
 - 54 12 ST3
 - 53 13 ST2
 - 52 14 ST1
 - 51 15 ST0

PLAYFIELD SWITCHES
(SHEET 2 OF 3)

- CJ-3
- 10 1 TEST BUTTON
 - 2
 - 3 KEY
 - 27 4 16
 - 30 5 15
 - 97 6 14
 - 21 7 13
 - 20 8 12
 - 65 9 11
 - 15 10 10
 - 11
 - 35 12 ST3
 - 74 13 ST2
 - 14 14 ST1
 - 13 15 ST0

CABINET SWITCHES

- CJ-2
- 30 1 D1J1-16 + D2J1-16
 - 14 2 D1J1-3, D1J1-14, D2J1-3
 - 18 3 D1J1-5, D2J1-5, D1J1-11
 - 21 4 D1J1-7, D2J1-7, D2J1-14
 - 23 5 D1J1-8, D2J1-8, D2J1-11
 - 20 6 D1J1-6, D2J1-6
 - 15 7 D1J1-4, D2J1-4
 - 13 8 D1J1-2, D2J1-2
 - 12 9 D1J1-1, D2J1-1
 - 10 N/U
 - 11 N/U
 - 38 12 D2J1-9
 - 24 13 D1J1-9, D1J1-21, D2J1-21
 - 35 14 D1J1-20, D2J1-20
 - 15 KEY
 - 34 16 D1J1-19, D2J1-19
 - 32 17 D1J1-18, D2J1-18
 - 31 18 D1J1-17, D2J1-17
 - 19 N/U

DIGITAL DISPLAY OUTPUTS
(SHEET 3 OF 3)

- CJ-1
- 30 1 PJ3-1
 - 2
 - 65 3 PJ3-15
 - 67 4 PJ3-3
 - 5 KEY
 - 98 6 PJ3-7
 - 58 7 PJ3-4
 - 13 8 PJ3-11
 - 9
 - 70 10 PJ3-12
 - 70 11 PJ3-13
 - 12

- CJ-14
- 1
 - 20 2 PJ3-6
 - 3 KEY
 - 20 4 PJ3-5
 - 25 5 PJ3-8
 - 13 6 PJ3-9
 - 13 7 PJ3-2

POWER INPUTS
(SHEET 1 OF 3)

BACKBOX CABLE DISTRIBUTION

NOTES:	BALLY MIDWAY MFG. CO.	
H. STONE	DUNGEONS AND DRAGONS	
10/5/87	BACKBOX	
	M051-00H06-A006	
	SHEET 2 OF 3	REV A

E

5-7
5-8
5-9
5-10

4-6

5-15

3-7

Y

4-4

J2

3 2 1

50 80

CABINET
& VOLUME CONTROL

BACKBOX (SHEET 3 OF 3)

TO BACKBOX (PAGE 2 OF 3)

COLOR CODE

- | | |
|------------|--------------|
| 1 - RED | 6 - BROWN |
| 2 - BLUE | 7 - ORANGE |
| 3 - YELLOW | 8 - BLACK |
| 4 - GREEN | 9 - GRAY |
| 5 - WHITE | 0 - NO TRACE |
| | 11 - VIOLET |

DISPLAY MODULES & SOUND MODULE

NOTES:	BALLY MIDWAY MFG. CO.	
W. STONE	DUNGEONS AND DRAGONS	
10/5/87	BACKBOX	
	M051-00H06-A006	
	SHEET 3 OF 3	REV A

87 OCT 87 14152 USER/HES/DRAGON/BACKBOX 3, DRAW

DIGITAL DISPLAY MODULES-D1 & D2

PLYR 1&2

PLYR 3&4

SOUND MOD

D1J1

D2J1

SJ1


12	—	CJ2-9	1
13	—	CJ2-8	2
14	—	CJ2-2	3
15	—	CJ2-7	4
18	—	CJ2-3	5
20	—	CJ2-6	6
21	—	CJ2-4	7
23	—	CJ2-5	8
24	—	CJ2-13	9
KEY	—	KEY	10
18	—	CJ2-3	11
28	—	PJ4-7	12
N/U	—	N/U	13
14	—	CJ2-2	14
N/U	—	N/U	15
30	—	CJ2-1	16
31	—	CJ2-18	17
32	—	CJ2-17	18
34	—	CJ2-16	19
35	—	CJ2-14	20
24	—	CJ2-13	21
40	—	PJ4-6	22
10	—	PJ4-9	23
	—	N/U	24


12	—	CJ2-9	1
13	—	CJ2-8	2
14	—	CJ2-2	3
15	—	CJ2-7	4
18	—	CJ2-3	5
20	—	CJ2-6	6
21	—	CJ2-4	7
23	—	CJ2-5	8
30	—	CJ2-12	9
KEY	—	KEY	10
23	—	CJ2-5	11
28	—	PJ4-7	12
N/U	—	N/U	13
21	—	CJ2-4	14
N/U	—	N/U	15
30	—	CJ2-1	16
31	—	CJ2-18	17
32	—	CJ2-17	18
34	—	CJ2-16	19
35	—	CJ2-14	20
24	—	CJ2-13	21
40	—	PJ4-6	22
10	—	PJ4-9	23
	—	N/U	24

20	1
25	2
28	3
21	4
	5
40	6
	7
27	8
	9
98	10
	11
	12
	13
	14
50	15

6 5

(SPEAKER)





©1985 BALLY MIDWAY MFG. CO. PAT. PENDING
 ALL RIGHTS RESERVED
 6803 PINBALL POWER MODULE A080-91785-D000

THIS DWG IS CONFIDENTIAL & PROPERTY OF MIDWAY MFG. CO

DIM. TOLERANCES UNLESS OTHERWISE SPEC. CONCENTRICITY T.I.R. .002 FRACTIONAL ± .1/64 DECIMAL ± .005 HOLE DIA. + .002 - .000 ANGLE ± 1/2° DO NOT SCALE DWG.		FIRST USED ON DWN CL DATE 04/08/86 SCALE		MIDWAY MFG. CO. FRANKLIN PARK, ILL. 60131 A BALLY CO.	
SPEC. CHG. MAT'L ELEC CHG. Cmm FINISH		ASSY DRAWING 6803 PINBALL PWR MODULE A084-91785-D000		PART NO M05-1-00-C53-D00-1	
				REVISIONS	

POWER MODULE
85-D000
53-D001

<u>DESIGNATION</u>	<u>DESCRIPTION</u>
JW1 - JW16	ZERO OHM RES. JUMPER
TP1 - TP10	TEST POINTS
F1*	5 AMP 3AG FUSE
F2	3/4 AMP 3AG FUSE
F3	6 AMP 3AG FUSE
F4, F5	8 AMP 3AG FUSE
F6, F7	15 AMP 3AG FUSE
F8	3/16 AMP 8AG FUSE
FC1A - FC3B, FC8A	FUSE CLIPS
FC8B	
FC4A - FC7B	FUSE CLIPS
J1	12 PIN M-N-L CONN. FEMALE
J2	6 PIN M-N-L CONN. MALE
J3	15 PIN M-N-L CONN. MALE
J4	9 PIN M-N-L CONN. MALE
J5	12 PIN M-N-L CONN. MALE
J6	2 PIN M-N-L CONN. MALE
6803 POWER MODULE	P.C. BOARD

4-23-86 REV. 1.0 FIXED R2, R6

* TWO FLIPPER GAMES ONLY - SEE SCHEMATIC

DESIGNATION LIST

<u>DESIGNATION</u>	<u>DESCRIPTION</u>
C1	11,000uf 20V ELEC.
P/O C1	TY-WRAP
P/O C1	SOLDER LUG
P/O C1	WIRE 20AWG
C2	160uf 350V ELEC.
P/O C2	TY-WRAP
C3	2uf 25V ELEC.
C4, C5	.1uf 25V CER.
C6, C7	.01uf 500V CER.
R1	600 OHM 10W
R2	100K 1W 5%
R3	2.2 OHM 1/4W 5%
R4	100 OHM 1/2W 5%
R5	22K 1/2W 5%
R6	100K 1/4W 5%
R7	390 OHM 1/4W 5%
R8	1.2K 1/4W 5%
R9	82K 1/2W 5%
R10	8.2K 1/4W 5%
VR1	0 - 25K 1/4W POT.
D1 - D4	MR751
D5 - D9	IN4004
D10	IN5275A ZENER
BR1	KBPC-35-02-W
P/O BR1	BRIDGE SPACER
O1	2N3584
P/O O1	SHIELD
P/O O1	HEX SPACER
P/O O1	6-32 X 5 SCREW
P/O O1	6-32 X 12 SCREW
P/O O1	LOCKWASHER EXT.
P/O O1	LOCKWASHER INT.
P/O O1	FLAT WASHER
P/O O1	6-32 HEX NUT
P/O O1	LABEL - CAUTION HIGH VOLT.
P/O O1	HEATSINK 2
P/O O1	INSULATOR TO-66
Q2, Q3	2N3440
P/O Q2, Q3	INSULATOR TO-5
P/O Q3	HEATSINK 3
U1	78H05C REG.
P/O U1	6-32 X 12 SCREW
P/O U1	6-32 HEX NUT
P/O U1	LOCKWASHER EXT.
P/O U1	FLAT WASHER
P/O U1	HEATSINK 1
P/O U1	INSULATOR TO-3
VA1	VARISTOR

6803 PINBALL POWER MODULE
A084-91785-D000
M051-00C53-D001

CROSS REFERENCE LIST


<u>DESCRIPTION</u>	<u>QTY.</u>	<u>DESIGNATION NO.</u>	<u>PART NOS.</u>
.01UF 500V CER.	2	C6,C7	0360-00800-0013
.1UF 25V CER.	2	C4,C5	0360-00800-0026
2UF 25V ELEC.	1	C3	0360-00800-0019
160UF 350V ELEC.	1	C2	0360-00800-0020
11,000UF 20V ELEC.	1	C1	0360-00800-0024
2.2 OHM 1/4W 5%	1	R3	100E-00005-0003
100 OHM 1/2W 5%	1	R4	100E-00006-0021
390 OHM 1/4W 5%	1	R7	100E-00005-0049
600 OHM 10W 10%	1	R1	100E-00002-0049
1.2K 1/4W 5%	1	R8	100E-00005-0063
8.2K 1/4W 5%	1	R10	100E-00005-0086
22K 1/2W 5%	1	R5	100E-00006-0065
82K 1/2W 5%	1	R9	100E-00006-0072
100K 1/4W 5%	1	R6	100E-00005-0115
100K 1W 5%	1	R2	100E-00007-0037
0-25K 1/4W POT	1	VR1	0360-00804-0004
MR 751	4	D1-D4	103E-00003-0016
1N4004	5	D5-D9	103E-00003-0005
1N5275	1	D10	103E-00001-0027
KBPC-35-02-W	1	BR1	103E-00005-0005
2N3440	2	Q2,Q3	104E-00003-0002
2N3584	1	Q1	104E-00005-0002
78H05C REG	1	U1	0360-00803-0021
VARISTOR METAL OXIDE 60V	1	VA1	115E-00001-0002
TY-WRAP	4	P/O C1,C2	0017-00042-0048
ZERO OHM RES. JUMPER	16	JW1-JW16	117E-00001-0001
TEST POINTS	10	TP1-TP10	0017-00007-0131
SOLDER LUG	2	P/O C1	0017-00021-0257
JUMPER WIRE 20AWG	2	P/O C1	0017-00033-0448
INSULATOR T0-3	1	P/O U1	0017-00042-0119
INSULATOR T0-5	2	P/O Q2,Q3	0017-00042-0151
INSULATOR T0-66	1	P/O Q1	0017-00042-0158
HEX SPACER	2	P/O Q1	0017-00042-0248
SHIELD	1	P/O Q1	0365-00952-0000
HEATSINK 1	1	P/O U1	112E-00001-0003
HEATSINK 2	1	P/O Q1	112E-00001-0002
HEATSINK 3	1	P/O Q3	112E-00001-0004
BRIDGE SPACER	1	P/O BR1	118E-00001-0001
6-32 X 12 SCREW	4	P/O Q1,U1	0017-00101-0132
6-32 X 5 SCREW	2	P/O Q1	0017-00101-0555
6-32 HEX NUT	4	P/O Q1,U1	0017-00103-0005
LOCKWASHER INT.	4	P/O Q1,	0017-00104-0008
LOCKWASHER EXT.	4	P/O Q1,U1	0017-00104-0009
FLAT WASHER	4	P/O Q1,U1	0017-00104-0106
FUSE CLIP	8	FC1A-FC3B, FC8A,FC8B	0017-00071-0033
FUSE CLIP	8	FC4A-FC7A	0017-00071-0034
3/16 AMP 8AG FUSE	1	F8	0017-00003-0206
3/4 AMP 3AG FUSE	1	F2	0017-00003-0010
5 AMP 3AG FUSE	1	F1*	0017-00003-0175
6 AMP 3AG FUSE	1	F3	0017-00003-0008

CROSS REFERENCE LIST

<u>DESCRIPTION</u>	<u>QTY.</u>	<u>DESIGNATION NO.</u>	<u>PART NOS.</u>
8 AMP 3AG FUSE	2	F4,F5	0017-00003-0387
15 AMP 3AG FUSE	2	F6,F7	0017-00003-0011
12 PIN M-N-L CONN. FEMALE	1	J1	0017-00021-0532
6 PIN M-N-L CONN. MALE	1	J2	0017-00021-0424
15 PIN M-N-L CONN. MALE	1	J3	0017-00021-0434
9 PIN M-N-L CONN. MALE	1	J4	0017-00021-0425
12 PIN M-N-L CONN. MALE	1	J5	0017-00021-0426
2 PIN M-N-L CONN. MALE	1	J6	0017-00021-0488
6803 POWER MODULE P.C.B.	1		A080-91785-D000

* TWO FLIPPER GAMES ONLY - SEE SCHEMATIC

9 TP8
VAC 6.3 VAC




2-11

8/14/86 REV 1 CHANGED C6, C7 TO .01 UF. CMM

D FU1 SHOULD BE 6AMP
FU1 SHOULD BE 7AMP


NOTES: R. KOHAN	BALLY MIDWAY MFG. CO.	
	1PER	6803 PINBALL PWR MODULE
	03/11/86	SCHEMATIC DRAWING
		A004-91785-D000
		M051-00C53-D002
	SHEET 1 OF 1	REV

B6 09132 /USER/DAN/POWER 1. DRAW




NOTE

* WHEN 3FLIPPERS ARE U
WHEN 4FLIPPERS ARE USE



DIM. TOLERANCES			
UNLESS OTHERWISE SPEC.			
FRACTIONAL	± 1/64	CONCENTRICITY T.I.R.	± .002
DECIMAL	± .005	HOLE DIA.	± .002 - .000
ANGLE	± 1/2°		
DO NOT SCALE DWG.			
FIRST USED ON		DATE	
DRN CL		04/08/86	
MECH CHK		MATE	
ELEC CHK		FINISH	
Cmm			



CONFIDENTIAL & PROPERTY OF MIDWAY MFG. CO.

MIDWAY MFG. CO.
FRANKLIN PK., IL 60131 A BALLY CO.

ASSY DRAWING
6803 CONTROL BD.
A084-91786-G000

REVISIONS	
PART NO	M0-5-1-0-0-C-5-3-G-0-0-3

BOARD
-G000
-G003

CROSS REFERENCE LIST

DESCRIPTION	QTY.	DESIGNATION NO.	PART NOS.
7.5 1/4W 5%	1	R5	100E-00005-0085
9.1 1/4W 5%	1	R4	100E-00005-0087
10K 1/4W 5%	4	R12, R13, R30, R33	100E-00005-0088
15K 1/4W 5%	2	R31, R34	100E-00005-0092
39K 1/4W 5%	1	R7	100E-00005-0102
47K 1/4W 5%	2	R10, R11	100E-00005-0104
56K 1/4W 5%	14	R62, R64, R66, R68 R70, R125-R132, R229	100E-00005-0106
62K 1/4W 5%	1	R15	100E-00005-0107
82K 1/4W 5%	1	R14	100E-00005-0112
100K 1/4W 5%	2	R26, R237	100E-00005-0115
270K 1/4W 5%	1	R77	100E-00005-0126
82 OHM 1W 10%	1	R27	100E-00007-0014
IN958R ZENER	1	D1	103E-00001-0002
IN4004	20	D19-D38	103E-00003-0005
IN4148	13	D3, D6, D9-D18, D39	103E-00002-0005
IN4606	5	D2, D4, D5, D7, D8	103E-00002-0006
2N3904	3	Q2, Q4, Q6	104E-00001-0006
2N4403	2	Q3, Q5	104E-00002-0006
2N5060	35	Q23-Q33, Q37, Q41-Q50, Q54-Q64, Q69, Q70	104E-00015-0001
2N5305	1	Q1	104E-00007-0003
MCR106-1	10	Q34-Q36, Q51-Q53 Q65-Q68	0360-00802-0009
SE9302	19	Q7-Q22, Q38-Q40	0360-00802-0008
4011	1	U11	0360-00803-0010
4502	1	U13	0360-00803-0005
4514B	3	U15-U17	0360-00803-0013
4584	1	U12	0066-090RX-XXDX
6116 RAM	1	U4	0365-00803-0013
6803 MPU	1	U1	0360-00803-0048
6821 PIA	2	U7, U8	0360-00803-0017
74LS04	1	U10	0A15-00803-0010
74LS10	1	U9	0A89-00803-0007
75LS154	1	U14	0360-00803-0024
74HCT245	1	U5	0365-00803-0014
74LS373	1	U6	0A89-00803-0006
CA3081	3	U18-U20	0360-00803-0007
3.580 MHz CRYSTAL	1	XTAL-1	109E-00001-0003
LED GREEN	1	LED 1	0017-00007-0131
TEST POINTS	7	TP1-TP7	0017-00007-0131
SWITCH P.B.	1	SW1	0017-00032-0038
BATTERY 3.6V	1	BATT-1	0017-00003-0172
ZERO OHM RES. JUMPER	5	JW2, JW4, JW6, JW8, JW10	117E-00001-0001
RELAY 48VDC	1	K1	114E-00001-0011
40 PIN I.C. SOCKET	3	XU1, XU7, XU8	110E-00001-0011
28 PIN I.C. SOCKET	2	XU2, XU3	110E-00001-0010
24 PIN I.C. SOCKET	1	XU4	110E-00001-0007
FERRITE BEAD	4	FR1-FR4	0316-00804-0002

CROSS REFERENCE LIST

<u>DESCRIPTION</u>	<u>QTY.</u>	<u>DESIGNATION NO.</u>	<u>PART NOS.</u>
27pf 50V CER.	2	C2, C3	0360-00800-0052
47pf 50V CER.	1	C7	0360-00800-0027
390pf 50V CER.	25	C24-C30, C57-C71	0360-00800-0001
		C88-C90	
470pf 1KV CER.	27	C17-C23, C31-C36,	0307-00800-0008
		C38-C41, C48-C56, C91	
.002uf 1KV CER.	19	C44-C47, C73-C87	0360-00800-0012
.003uf 1KV CER.	1	C43	0360-00800-0025
.01uf 50V CER.	24	C6, C9, C10, C12, C13	0365-00800-0014
		C15, C16, C42, CP1-CP16	
.05uf 16V CER.	1	C37	0360-00800-0006
.1uf 50V CER.	1	C4	0360-00800-0058
4.7uf 25V TANT	2	C5, C14	0360-00800-0008
6.8uf 25V TANT	1	C1	0360-00800-0048
470uf 16V ELEC	1	C8	0360-00800-0022
470uf 25V ELEC	1	C11	0360-00800-0024
82 OHM 1/4W 5%	1	R9	100E-00005-0031
100 OHM 1/4W 5%	1	R8	100E-00005-0033
110 OHM 1/4W 5%	1	R83	100E-00005-0034
120 OHM 1/4W 5%	21	R24, R85, R87, R89,	100E-00005-0035
		R91, R121, R136-R138,	
		R151-R155, R165-R168,	
		R191-R193	
270 OHM 1/4W 5%	1	R28	100E-00005-0044
330 OHM 1/4W 5%	23	R92-R95, R139-R141,	100E-00005-0047
		R156-R160, R169-R172,	
		R194-R196, R231-R234	
470 OHM 1/4W 5%	9	R96-R104	100E-00005-0051
560 OHM 1/4W 5%	1	R1	100E-00005-0054
680 OHM 1/4W 5%	1	R25	100E-00005-0056
750 OHM 1/4W 5%	1	R19	100E-00005-0057
910 OHM 1/4W 5%	1	R18	100E-00005-0059
1K 1/4W 5%	3	R3, R29, R32	100E-00005-0061
1.2K 1/4W 5%	60	R44-R50, R59-R61, R63,	100E-00005-0063
		R65, R67, R69, R71-R76	
		R78-R82, R105-R119, R122	
		R133-R135, R146-R150,	
		R161-R164, R188-R190,	
		R227, R228, R230, R236	
		R20	
1.5K 1/4W 5%	1	R123, R173-R187	100E-00005-0065
2K 1/4W 5%	46	R197-R226	100E-00005-0068
		R2, R6	
2.7K 1/4W 5%	2	R17	100E-00005-0071
3K 1/4W 5%	1	R21-R23, R35, R51-R58,	100E-00005-0073
3.3K 1/4W 5%	18	R124, R142-R145, R235	100E-00005-0074
		R84, R86, R88, R90	
3.9K 1/4W 5%	4	R36-R43	100E-00005-0077
4.7K 1/4W 5%	8	R16	100E-00005-0079
5.6 1/4W 5%	1		100E-00005-0082

DESIGNATION LIST

<u>DESIGNATION</u>	<u>DESCRIPTION</u>	<u>DESIGNATION</u>	<u>DESCRIPTION</u>	<u>DESIGNATION</u>
C1	6.8UF 25V TANT.	R28	270 OHM 1/4W 5%	R165
C2,C3	27PF 50V CER.	R29	1K 1/4W 5%	R169
C4	.1UF 50V CER.	R30	10K 1/4W 5%	R173
C5	4.7UF 25V TANT.	R31	15K 1/4W 5%	R188
C6	.01UF 50V CER.	R32	1K 1/4W 5%	R191
C7	47PF 50V CER.	R33	10K 1/4W 5%	R194
C8	470UF 16V ELEC.	R34	15K 1/4W 5%	R197
C9,C10	.01UF 50V CER.	R35	3.3K 1/4W 5%	R227
C11	470UF 25V ELEC.	R36 - R43	4.7K 1/4W 5%	R229
C12,C13	.01UF 50V CER.	R44 - R50	1.2K 1/4W 5%	R230
C14	4.7UF 25V TANT.	R51 - R58	3.3K 1/4W 5%	R231
C15,C16	.01UF 50V CER.	R59 - R61	1.2K 1/4W 5%	R235
C17 - C23	470PF 1KV CER.	R62	56K 1/4W 5%	R236
C24 - C30	390PF 50V CER.	R63	1.2K 1/4W 5%	R237
C31 - C36	470PF 1KV CER.	R64	56K 1/4W 5%	D1
C37	.05UF 16V CER.	R65	1.2K 1/4W 5%	D2
C38 - C41	470PF 1KV CER.	R66	56K 1/4W 5%	D3
C42	.01UF 50V CER.	R67	1.2K 1/4W 5%	D4,D
C43	.003UF 1KV CER.	R68	56K 1/4W 5%	D6
C44 - C47	.002UF 1KV CER.	R69	1.2K 1/4W 5%	D7,D
C48 - C56	470PF 1KV CER.	R70	56K 1/4W 5%	D9 -
C57 - C71	390PF 50V CER.	R71 - R76	1.2K 1/4W 5%	D19
C73 - C87	.002 1KV CER.	R77	270K 1/4W 5%	D39
C88 - C90	390PF 50V CER.	R78 - R82	1.2K 1/4W 5%	Q1
C91	470PF 1KV CER.	R83	110 OHM 1/4W 5%	Q2
CP1 - CP16	.01 50V CER.	R84	3.9K 1/4W 5%	Q3
R1	560 OHM 1/4W 5%	R85	120 OHM 1/4W 5%	Q4
R2	2.7K 1/4W 5%	R86	3.9K 1/4W 5%	Q5
R3	1K 1/4W 5%	R87	120 OHM 1/4W 5%	Q6
R4	9.1K 1/4W 5%	R88	3.9K 1/4W 5%	Q7 -
R5	7.5K 1/4W 5%	R89	120 OHM 1/4W 5%	Q23
R6	2.7K 1/4W 5%	R90	3.9K 1/4W 5%	Q34
R7	39K 1/4W 5%	R91	120 OHM 1/4W 5%	Q37
R8	100 OHM 1/4W 5%	R92 - R95	330 OHM 1/4W 5%	Q38
R9	82 OHM 1/4W 5%	R96 - R104	470 OHM 1/4W 5%	Q41
R10,R11	47K 1/4W 5%	R105 - R119	1.2K 1/4W 5%	Q51
R12,R13	10K 1/4W 5%	R121	120 OHM 1/4W 5%	Q54
R14	82K 1/4W 5%	R122	1.2K 1/4W 5%	Q65
R15	62K 1/4W 5%	R123	2K 1/4W 5%	Q69,C
R16	5.6K 1/4W 5%	R124	3.3K 1/4W 5%	U1
R17	3K 1/4W 5%	R125 - R132	56K 1/4W 5%	U4
R18	910 OHM 1/4W 5%	R133 - R135	1.2K 1/4W 5%	U5
R19	750 OHM 1/4W 5%	R136 - R138	120 OHM 1/4W 5%	U6
R20	1.5K 1/4W 5%	R139 - R141	330 OHM 1/4W 5%	U7,U8
R21 - R23	3.3K 1/4W 5%	R142 - R145	3.3K 1/4W 5%	U9
R24	120 OHM 1/4W 5%	R146 - R150	1.2K 1/4W 5%	U10
R25	680 OHM 1/4W 5%	R151 - R155	120 OHM 1/4W 5%	U11
R26	100K 1/4W 5%	R156 - R160	330 OHM 1/4W 5%	U12
R27	82 OHM 1W 10%	R161 - R164	1.2K OHM 1/4W 5%	U13
				U14

CONTROL BOARD
786-G000
C53-G003

DESIGNATION	DESCRIPTION	DESIGNATION	DESCRIPTION
R168	120 OHM 1/4W 5%	U15 - U17	4514B
R172	330 OHM 1/4W 5%	U18 - U20	CA3081
R187	2K 1/4W 5%	XTAL-1	3.580 MHZ CRYSTAL
R190	1.2K 1/4W 5%	LED 1	LED GREEN
R193	120 OHM 1/4W 5%	TP1 - TP7	TEST POINTS
R196	330 OHM 1/4W 5%	SW1	SWITCH P.B.
R226	2K 1/4W 5%	BATT-1	BATTERY 3.6V
R228	1.2K 1/4W 5%	JW2	ZERO OHM RES. JUMPER
	56K 1/4W 5%	JW4	ZERO OHM RES. JUMPER
	1.2K 1/4W 5%	JW6	ZERO OHM RES. JUMPER
R234	330 OHM 1/4W 5%	JW8	ZERO OHM RES. JUMPER
	3.3K 1/4W 5%	JW10	ZERO OHM RES. JUMPER
	1.2K 1/4W 5%	K1	RELAY 48V DC
	100K OHM 1/4W 5%	XU1, XU7, XU8	40 PIN IC SOCKET
	1N958B	XU2, XU3	28 PIN IC SOCKET
	1N4606	XU4	24 PIN IC SOCKET
	1N4148	FB1 - FB4	FERRITE BEAD
	1N4606	J1	11 - .045 SQ. PINS
	1N4148	J2	18 - .025 SQ. PINS
	1N4606	J3	14 - .025 SQ. PINS
	1N4148	J4	14 - .025 SQ. PINS
D38	1N4004	J5	14 - .025 SQ. PINS
	1N4148	J6	8 - .045 SQ. PINS
	2N5305	J7	7 - .045 SQ. PINS
	2N3904	J8	6 - .045 SQ. PINS
	2N4403	J9	10 - .045 SQ. PINS
	2N3904	J10	18 - .025 SQ. PINS
	2N4403	J11	17 - .025 SQ. PINS
	2N3904	J12	16 - .025 SQ. PINS
	SE9302	J13	12 - .025 SQ. PINS
	2N5060	J14	5 - .045 SQ. PINS
	MCR 106-1	P/O BATT-1	TY-WRAP
	2N5060	6803 CONTROL BD.	P.C. BOARD
	SE9302		
	2N5060		
	MCR 106-1		
	2N5060		
	MCR 106-1		
	2N5060		
	6803		
	6116 RAM		
	74HCT245		
	74LS373		
	6821		
	74LS10		
	74LS04		
	4011		
	4584		
	4502		
	74LS154		

6803 CONTROL BOARD
A084-91786-G000
M051-000C53-G003

CROSS REFERENCE LIST


<u>DESCRIPTION</u>	<u>QTY.</u>	<u>DESIGNATION NO.</u>	<u>PART NOS.</u>
.025 SQ. PINS	123	J2, J3, J4, J5, J10, J11, J12, J13	0304-00804-0009
.045 SQ. PINS	47	J1, J6, J7, J8, J9, J14	0304-00804-0010
TY-WRAP	1	P/O BATT-1	0017-00042-0622
P.C. BOARD	1	6803 CONTROL BOARD	A080-91786-G000

4-23-86 REV. 1.0 Fixed Part Number for 470PF Cap.

NOTES:	BALLY MIDWAY MFG. CO.
R. KOHAN	6883 PINBALL CONTROL MODULE
	SCHEMATIC DRAWING
	A884-91786-6888
	M881-88C53-6884
	SHEET 1 OF 2 DCA

FOR 27321 JUL 3, 5
27641 JUL 5
271201 JUL 2, 4, 6


SHEET 3 OF 3





6-30-86 CORRECTED PIA ADDRESSING (AGAIN), CHM
6-27-86 AB/RS CORRECTED TO PINS, CHM


NOTES:
BALLY MIDWAY MFG. CO.
6803 PIA CONTROL MODULE
SCHEMATIC DRAWING
A884-91786-6088
M031-00153-6084

SHEET 2 OF 7 REV







NOTES:	BALLY MIDWAY MFG. CO.
R. KOHAN	6803 PINBALL CONTROL MODULE
	SCHEMATIC DRAWING
	8984-91786-5888
	NO. 1-88023-5884
SHEET 3 OF 7 REV	



NOTES:
 6803 PINBALL CONTROL MODULE
 SCHEMATIC DRAWING
 6803-91706-5800
 6803-90053-5804
 SHEET 3 OF 7 REV



NOTES:	
R. KOHAN	BALLY MIDWAY MFG. CO.
	6803 PINBALL CONTROL MODULE
	SCHEMATIC DRAWING
	A084-91786-6000
	M051-00C53-6004
	SHEET 7 OF 7 REV



DESIGNATION

DESIGNATION

CP1,CP2
CP3-CP13
C1
C2
C3-C5
C6
C7-C10
C11
C12
C13
C14
C15
C16
C17
C18
C19
C20
C21
C22
C23
C24
C25
C26,C27
C28-C30
C31
C32
C33,C34
C35
C36
C37
C38
C39

D1
D2
D3,D4
D5-D8
D9,D10

FB1-FB3

HS U15
HS U17

ICS U3
ICS U4
ICS U7
ICS U8
ICS U9-U14

© 1986 BALLY MIDWAY MFG. CO.
ALL RIGHTS RESERVED
PAT. PENDING

A080-91864-C000

REL FOR PRODUCTION
REVISIONS

USED ON Pinball

Bally / MIDWAY MFG. CO.

FRANKLIN PK. ILL

NO. REQ'D

ASSEMBLY DRAWING
SOUNDS DELUXE P.C.B.D.
A084-91864-C000

PART NO.

M051-00114-C153

SOUNDS DELUXE
A084-91864-C000

M051-00114-C154

Rev. 4

LIST

DESCRIPTION

.1 UF AX CER
.01 UF AX CER
.1 UF AX CER
10 UF RD TANT
NOT INSERTED
470 PF AX CER
100 PF AX CER
.01 UF AX CER
47 UF AX ELEC
470 PF AX CER
1 UF AX TANT
.01 UF AX CER
68 PF AX CER
.1 UF AX TANT
.001 UF AX CER
82 PF AX CER
10 UF AX TANT
1 UF AX TANT
.05 UF RD CER
470 UF AX ELEC
1000 UF AX ELEC
.1 UF AX CER
.22 UF AX CER
.1 UF AX CER
4700 UF AX ELEC
.01 UF AX CER
4.7 UF RD TANT
.01 UF AX CER
NOT INSERTED
10 UF AX TANT
.01 UF AX CER
.1 UF AX CER

NOT INSERTED
VR330
1N4004
NOT INSERTED
1N4004

FERRITE BEAD

HEATSINK TO-220
HEATSINK TO-220

64 PIN I.C. SOCKET
20 PIN I.C. SOCKET
40 PIN I.C. SOCKET
16 PIN I.C. SOCKET
28 PIN I.C. SOCKET

SOUNDS DELUXE
A084-91864-C000

M051-00114-C154

Rev. 4

DESIGNATION LIST

DESIGNATION

DESCRIPTION

INS U15, INS U17	SIL PAD THERMAL WASHER
J1,J2	AUTO INSERT PIN TIN .045 SQ.
JW1-JW12	JUMPER WIRE
L1,L2	10 UH INDUCTOR
LED 1	GREEN LED
MH U15	SCREW, 6-32
MH U15	NUT, 6-32
MH U15	WASHER, #6 STAR
MH U17	SCREW, 4-40
MH U17	NUT, 4-40
MH U17	WASHER, #4 STAR
Q1,Q2	2N5305
Q3-Q6	NOT INSERTED
R1-R8	4.7K OHM 1/4W CRBN
R9	NOT USED
R10-R12	NOT INSERTED
R13	10K OHM 1/4W CRBN
R14	100K OHM 1/4W CRBN
R15-R18	10K OHM 1/4W CRBN
R19	47K OHM 1/4W CRBN
R20	100 OHM 1/4W CRBN
R21-R23	4.7K OHM 1/4W CRBN
R24	2.7K OHM 1/4W CRBN
R25	180 OHM 1/4W CRBN
R26	68 OHM 1/4W CRBN
R27	62K OHM 1/4W CRBN
R28	120K OHM 1/4W CRBN
R29	75K OHM 1/4W CRBN
R30	33K OHM 1/4W CRBN
R31	18K OHM 1/4W CRBN
R32	33K OHM 1/4W CRBN
R33	47K OHM 1/4W CRBN
R34	150K OHM 1/4W CRBN
R35	82K OHM 1/4W CRBN
R36	150K OHM 1/4W CRBN
R37	200K OHM 1/4W CRBN
R38	1K OHM 1/4W CRBN
R39	33K OHM 1/4W CRBN
R40	430 OHM 1/4W CRBN
R41	220 OHM 1/4W CRBN
R42	2.2 OHM 1/4W CRBN

SOUNDS DELUXE

A084-91864-C000

M051-00114-C154

Rev. 4

	<u>QTY.</u>	<u>DESIGNATION</u>	<u>PART NUMBER</u>
	1	C16	0360-00800-0028
	1	C19	0E47-00800-0002
	4	C7-C10	0360-00800-0046
0%	2	C6,C13	0307-00800-0008
10%	1	C18	0E47-00800-0003
0%	1	C15	0E47-00800-0001
	15	CP3-CP13,C11,C32	0360-00800-0005
		C35,C38	
	1	C22	0360-00800-0006
	8	CP1,CP2,C1,C25,	0360-00800-0058
		C28-C30,C39	
	2	C26,C27	0360-00800-0057
	3	C14,C17,C21	0986-00800-1400
	2	C33,C34	0360-00800-0008
	3	C2,C20,C37	0986-00800-0700
	1	C12	0360-00800-0042
	1	C23	0360-00800-0021
	1	C24	0360-00800-0044
	1	C31	0360-00800-0023
	1	R43	100E-00005-0002
BN	1	R42	100E-00005-0003
N	1	R26	100E-00005-0029
BN	1	R20	100E-00005-0033
RN	1	R25	100E-00005-0039
BN	1	R41	100E-00005-0041
BN	1	R40	100E-00005-0050
N	1	R38	100E-00005-0061
RBN	1	R24	100E-00005-0071
RBN	12	R1-R8,R21-R23,R59	100E-00005-0079
BN	6	R13,R15-R18,R60	100E-00005-0088
BN	1	R31	100E-00005-0093
BN	3	R30,R32,R39	100E-00005-0100
BN	2	R19,R33	100E-00005-0104
BN	1	R27	100E-00005-0107
RN	1	R29	100E-00005-0110
BN	1	R35	100E-00005-0112
RBN	1	R14	100E-00005-0115
RBN	1	R28	100E-00005-0118
RBN	2	R34,R36	100E-00005-0120
RBN	1	R37	100E-00005-0123
	1	VR1	0360-00804-0024
	4	D3,D4,D9,D10	103E-00003-0005
	1	D2	0360-00801-0007

SOUNDS DELUXE
A084-91864-C000
M051-00114-C154

Rev. 4

DESIGNATION LIST

<u>DESIGNATION</u>	<u>DESCRIPTION</u>
R43	1 OHM 1/4W CRBN
R44-R58	NOT INSERTED
R59	4.7K OHM 1/4W CRBN
R60	10K OHM 1/4W CRBN
SW1	PC MTG. SWITCH
TP1, TP2	TEST POINT
U1	16 MHZ COSC
U2	74LS74
U3	MC68000G8 CPU
U4	PAL16L8A-2 SDOORO
U5	74LS05
U6	74F32
U7	MC6821
U8	AD7533 DAC
U9, U10	RAM 2K X 8
U11-U14	ROM/EPROM
U15	TDA2002
U16	LM3900
U17	MC7805 REG.
U18	TL7705
VR1	10K POT.

CROSS REFERENCE

DESCRIPTION


68 PF AX CER !
82 PF AX CER !
100 PF AX CER
470 PF AX CER
.001 UF AX CE
.01 UF AX CER
.01 UF AX CER
.05 UF RD CER
.1 UF AX CER
.22 UF AX CER
1 UF AX TANT
4.7 UF RD TAN
10 UF AX TANT
47 UF AX ELEC
470 UF AX ELE
1000 UF AX EL
4700 UF AX EL
1 OHM 1/4W CR
2.2 OHM 1/4W
68 OHM 1/4W C
100 OHM 1/4W
180 OHM 1/4W
220 OHM 1/4W
430 OHM 1/4W
1K OHM 1/4W C
2.7K OHM 1/4W
4.7K OHM 1/4W
10K OHM 1/4W
18K OHM 1/4W
33K OHM 1/4W
47K OHM 1/4W
62K OHM 1/4W
75K OHM 1/4W
82K OHM 1/4W
100K OHM 1/4W
120K OHM 1/4W
150K OHM 1/4W
200K OHM 1/4W
10K POT
1N4004
VR330

SOUNDS DELUXE
A084-91864-C000
M051-00114-C154


CROSS REFERENCE


DESCRIPTION	QTY.	DESIGNATION	PART NUMBER
2N5305	2	Q1,Q2	0360-00802-0012
74F32	1	U6	0304-00803-0059
74LS05	1	U5	0E47-00803-0002
74LS74	1	U2	0304-00803-0058
AD7533 DAC	1	U8	0304-00803-0055
16 MHZ COSC	1	U1	0304-00804-0008
LM3900	1	U16	0360-00803-0002
MC6821	1	U7	0304-00803-0054
MC68000 G8 CPU	1	U3	
MC7805 REG	1	U17	0360-00803-0050
PAL16L8A-2 SDOOR0	1	U4	0E47-00803-0001
RAM 2K X 8	2	U9,U10	0E47-00803-0003
TDA2002	1	U15	0360-00803-0009
TL7705AC	1	U18	0066-447RX-XXCX
ROM/EPROM	4	U11-U14	SEE ROM/EPROM SHEET
FERRITE BEAD	3	FB1-FB3	0316-00804-0002
10 UH INDUCTOR	2	L1,L2	0360-00804-0031
16 PIN I.C. SOCKET	1	ICS U8	110E-00001-0003
20 PIN I.C. SOCKET	1	ICS U4	110E-00001-0005
28 PIN I.C. SOCKET	6	ICS U9-ICS U14	110E-00001-0010
40 PIN I.C. SOCKET	1	ICS U7	110E-00001-0011
64 PIN I.C. SOCKET	1	ICS U3	110E-00001-0016
HEATSINK TO-220	1	HS U15	112E-00001-0011
HEATSINK TO-220	1	HS U17	0E47-00804-0001
SIL PAD THERMAL WASHER	2	INS U15, INS U17	0017-00042-0319
SCREW, 6-32	1	MH U15	0017-00101-0339
NUT, 6-32	1	MH U15	0017-00103-0005
WASHER, #6 STAR	1	MH U15	0017-00104-0009
SCREW, 4-40	1	MH U17	0017-00101-0731
NUT, 4-40	1	MH U17	0017-00103-0002
WASHER, #4 STAR	1	MH U17	0017-00104-0071
AUTO INSERT PIN	16	J1,J2	0304-00804-0010
TIN .045 SQ.			
JUMPER WIRE	12	JW1-JW12	117E-00001-0003
GREEN LED	1	LED 1	119E-00001-0001
TEST POINT	2	TP1,TP2	0017-00007-0131
PC MTG. SWITCH	1	SW1	0986-00804-3100
PC BOARD	1	--	A080-91864-C000

8/01/86 Rev. 1 - Changed Filter Values, C13,C15,C16,C18,C19,R39 CMM
8/05/86 Rev. 2 - Removed D1 CMM.
8/11/86 Rev. 3 - Added CP11-CP13 CMM.
8/15/86 Rev. 4 - Added ICS U13, ICS U14. Fixed Desig. list U5, U6.
Corrected qty. of Ferrite Bead.



11 AUG 86 14143 Z0807CNR/C80P1N 1. DRAW








NOTES:	BALLY MIDWAY NFG. CO.
C. HEINICK	
I PER	BOUNDS DELUXE
24 JULY 86	A004-91B64-C000
	M031-00114-C155
SHEET 6 OF 6	REV

25 JUL 85 1618Z /USER/CNN/CBDDPIN/1-0 1. DRAW

2-26

PRINTING - 40-107




DIM. TOLERANCES	FIRS
UNLESS OTHERWISE SPEC.	USEI
CONCENTRICITY T.I.R.002	DRN
FRACTIONAL ± 1/64	MECI
DECIMAL ± .005	ELEC.
HOLE DIA. + .002— .000	
ANGLE ± 1/2°	
DO NOT SCALE DWG.	

98

L DISPLY MODULE

TP3 GND

A080-91851-H000



PAT. PENDING

DISPLAY

© 1985 BALLY MIDWAY MFG. CO.
ALL RIGHTS RESERVED

THIS DWG. IS CONFIDENTIAL & PROPERTY OF BALLY/MIDWAY MFG. CO.

ON PIN BALL		Bally/MIDWAY MFG. CO.		REL. FOR PRODUCTION 5/15/87	
DATE 5/15/87		FRANKLIN PARK, IL 60131		REVISIONS	
SCALE FULL		ASSEMBLY DRAWING		PART NO.	
MATERIAL		DUAL DISPLAY MODULE		M-0-5-1-0-0-3-6-5-H-0-3-3	
FINISH		A084-91851-H000			

DUAL DISPLAY MODULE
A084-91851-H000
M051-00365-H042 (Page 3 of 5) REV. 1

DESCRIPTION

[illegible]**DESCRIPTION**

C1	.01UF 500V CER.
C2	100PF 50V AX. CER.
CP1, CP2	.01UF 50V CER.
D1	1M110ZS10 110V ZENER DIODE
D2,D3	1N4148 DIODE
Q1 - Q4	MPS-A-42 NPN XSTR
Q5	2N5401 PNP XSTR
Q6	MPS-A-42
Q7	2N5401
Q8	MPS-A-42
Q9	2N5401
Q10 - Q21	MPS-A-42
Q22 - Q24	2N5401
Q25	MPS-A-42
Q26	MPS-A-42
Q27	2N5401
Q28	MPS-A-42
Q29 - Q35	2N5401
Q36 - Q40	MPS-A-42
U1	74HC373 CMOS OCTAL LATCH
U2	14514 1-16 DECODER
DISPLAY 1	14 DIGIT, 9 SEGMENT GAS DISCHARGE DISPLAY
J1	.025 SQ. PINS
TP1, TP2, TP3	TEST LOOPS
	FOAM TAPE
	BUMPER
	DISPLAY MTG. CLIPS
	SCREWS
	DISPLAY MTG. PROCEDURE
	DUAL DISPLAY MODULE P.C.B.
M051-00365- A041	
A080-91851-H000	

DU
NO51-00365-

DESIGNATION LIST

<u>DESIGNATION NO.</u>	<u>DE</u>
R59	10
R60	10
R61	9.
R62	9.
R63	10
R64	9.
R65	10
R66	9.
R67	10
R68	9.
R69	10
R70	30
R71	2.
R72	30
R73	2.
R74	30
R75	2.
R76	1.
R77	82
R78	30
R79	1.
R80	82
R81	30
R82	30
R83	2.
R84	10
R85	9.
R86	30
R87	2.
R88	2.
R89	30
R90	30
R91	2.
R92	30
R93	2.
R94	30
R95	2.
R96	30
R97	2.
R98	10
R99	1M
R100	30
R101	2.
R102	10
R103	9.
R104	15
R105	10
R106	1M
R107	10
R108-R115	20
RM1	10

DUAL DISPLAY MODULE
A084-91851-H000
M051-00365-M042 (Page 4 of 5) REV. 1

CROSS REFERENCE LIST


DESCRIPTION	QTY.	DESIGNATION NO.	PART NOS.
510 OHM 1/4W 5% CARBON	1	R5	100E-00005-0053
820 OHM 1/4W 5% CARBON	7	R2,R8,R35,R46	100E-00005-0058
		R49,R77,R80	
1K 1/4W 5% CARBON	2	R39,R42	100E-00005-0061
1.5K 1/4W 5% CARBON	10	R1,R4,R7,R34,R38	100E-00005-0065
		R43,R45,R48	
		R76,R79	
2.2K 1/4W 5% CARBON	14	R18,R22,R26,R71	100E-00005-0069
		R73,R75,R83,R87	
		R88,R91,R93,R95	
		R97,R101	
9.1K 1/4W 5% CARBON	14	R16,R20,R24,R28	100E-00005-0087
		R30,R32,R58,R61	
		R62,R64,R66,R68	
		R85,R103	
10K 1/4W 5% CARBON	1	R107	100E-00005-0088
20K 1/4W 5% CARBON	14	R10-R15,R108-R115	100E-00005-0095
100K 1/4W 5% CARBON	2	R40,R41	100E-00005-0115
100K 1/4W 1% METAL FILM	15	R17,R21,R25,R29	100E-00001-0046
		R31,R33,R51,R59	
		R60,R63,R65,R67	
		R69,R84,R102	
150K 1/4W 5% CARBON	1	R104	100E-00005-0120
300K 1/4W 5% CARBON	24	R3,R6,R9,R19,R23	100E-00005-0127
		R27,R36,R37,R44,	
		R47,R50,R70,R72,	
		R74,R78,R81,R82,	
		R86,R89,R90,R92,	
		R94,R96,R100	
1.0M OHM 1/4W 5% CARBON	2	R99,R106	100E-00005-0140
2.2M OHM 1/4W 5% CARBON	6	R52 - R57	100E-00005-0147
100K 10 PIN SIP	1	RM1	102E-00004-0045
10.0M OHM 1/4W 5% CARBON	2	R98,R105	100E-00005-0162
100PF AX. CER.	1	C2	0639-00800-0003
.01UF	2	CP1,CP2	0360-00800-0005
.01UF 500V	1	C1	0360-00800-0013
1N4148	2	D2,D3	103E-00002-0005
1M110ZS10 110V ZENER DIODE	1	D1	103E-00001-0028
2N5401 PNP XSTR	14	Q5,Q7,Q9,Q22,Q23	0360-00802-0006
		Q24,Q27,Q29,Q30	
		Q31,Q32,Q33,Q34	
		Q35	
MPS-A-42 NPN XSTR	26	Q1-Q4,Q6,Q8,Q10-	0360-00802-0007
		Q21,Q25,Q26,Q28	
		Q36-Q40	
14514 1-16 DECODER	1	U2	0360-00803-0013
74HC373 OCTAL LATCH	1	U1	0365-00803-0015
.025SQ. PINS	23	J1	0304-00804-0009
14 DIGIT, 9 SEGMENT			
GAS DISCHARGE DISPLAY	1	DISPLAY 1	119E-00002-0006
TEST LOOPS	3	TP1 - TP3	0017-00007-0131

DUAL DISPLAY MODULE
A084-91851-H000
M051-00365-H042 (Page 5 of 5) REV. 1

CROSS REFERENCE LIST

<u>DESCRIPTION</u>	<u>QTY.</u>	<u>DESIGNATION NO.</u>	<u>PART NOS.</u>
FOAM TAPE	2		0017-00081-0289
BUMPER	1		0017-00041-0598
DISPLAY MTG. CLIP	2		0365-00174-00XF
SCREW	2		0017-00101-0175
DISPLAY MTG. PROCEDURE	1		M051-00365-A041
DUAL DISPLAY MODULE PCB	1		A080-91851-H000


5/20/87 REV. 1 - CORRECTION TO DISPLAY MTG. PROCEDURE PART NO. *955*



NOTES:
 1. REVISED FROM ORIGINAL 5/1/67
 2. BALLY RICHARD WFS, CO.
 3. DUAL DISPLAY MODULE
 4. 8004-91831-10000
 5. 8004-91831-10000
 6. 8004-91831-10000
 7. 8004-91831-10000
 8. 8004-91831-10000
 9. 8004-91831-10000
 10. 8004-91831-10000
 11. 8004-91831-10000
 12. 8004-91831-10000
 13. 8004-91831-10000
 14. 8004-91831-10000
 15. 8004-91831-10000
 16. 8004-91831-10000
 17. 8004-91831-10000
 18. 8004-91831-10000
 19. 8004-91831-10000
 20. 8004-91831-10000
 21. 8004-91831-10000
 22. 8004-91831-10000
 23. 8004-91831-10000
 24. 8004-91831-10000
 25. 8004-91831-10000
 26. 8004-91831-10000
 27. 8004-91831-10000
 28. 8004-91831-10000
 29. 8004-91831-10000
 30. 8004-91831-10000
 31. 8004-91831-10000
 32. 8004-91831-10000
 33. 8004-91831-10000
 34. 8004-91831-10000
 35. 8004-91831-10000
 36. 8004-91831-10000
 37. 8004-91831-10000
 38. 8004-91831-10000
 39. 8004-91831-10000
 40. 8004-91831-10000
 41. 8004-91831-10000
 42. 8004-91831-10000
 43. 8004-91831-10000
 44. 8004-91831-10000
 45. 8004-91831-10000
 46. 8004-91831-10000
 47. 8004-91831-10000
 48. 8004-91831-10000
 49. 8004-91831-10000
 50. 8004-91831-10000
 51. 8004-91831-10000
 52. 8004-91831-10000
 53. 8004-91831-10000
 54. 8004-91831-10000
 55. 8004-91831-10000
 56. 8004-91831-10000
 57. 8004-91831-10000
 58. 8004-91831-10000
 59. 8004-91831-10000
 60. 8004-91831-10000
 61. 8004-91831-10000
 62. 8004-91831-10000
 63. 8004-91831-10000
 64. 8004-91831-10000
 65. 8004-91831-10000
 66. 8004-91831-10000
 67. 8004-91831-10000
 68. 8004-91831-10000
 69. 8004-91831-10000
 70. 8004-91831-10000
 71. 8004-91831-10000
 72. 8004-91831-10000
 73. 8004-91831-10000
 74. 8004-91831-10000
 75. 8004-91831-10000
 76. 8004-91831-10000
 77. 8004-91831-10000
 78. 8004-91831-10000
 79. 8004-91831-10000
 80. 8004-91831-10000
 81. 8004-91831-10000
 82. 8004-91831-10000
 83. 8004-91831-10000
 84. 8004-91831-10000
 85. 8004-91831-10000
 86. 8004-91831-10000
 87. 8004-91831-10000
 88. 8004-91831-10000
 89. 8004-91831-10000
 90. 8004-91831-10000
 91. 8004-91831-10000
 92. 8004-91831-10000
 93. 8004-91831-10000
 94. 8004-91831-10000
 95. 8004-91831-10000
 96. 8004-91831-10000
 97. 8004-91831-10000
 98. 8004-91831-10000
 99. 8004-91831-10000
 100. 8004-91831-10000

BALLY MIDWAY MFG. CO.
A080-91901-A000

PDW-1 J1





J2 PDW-1

CROSS REFERENCE/DESIGNATION LIST
FOR BRIGHT LIGHTS FUSE BOARD
M051-00114-A211 / REV. 1

QTY.	DESCRIPTION	PART NO.	DESIGNATION
32	PCR FUSE CLIPS	0017-00071-0034	F1-F16 (2 1/2")
1	17 POS. CONNECTOR KK100	0017-00021-1888	J2
1	9 POS. CONNECTOR KK100	0017-00021-1887	J1
1	RAW PC BOARD	A080-91901-A000	

REF:

LAYOUT/ASSEMBLY DRAWING M051-00114-A210
SCHEMATIC DRAWING M051-00114-A212
REV. 1 - CHANGED TO KK100 HEADERS 9/17/87 JBB



10/1/8

NOTES:	
J. BOYDSTON	
10-07-87	
BRIGHT LIGHTS FUSE PCB	
M051-00114-A212	
SHEET 1 OF 1 REV	

ID DRIVER LOCATIONS LISTING
00H06-A012

VER LOCATIONS

SE	WIRE	DESCRIPTION
18		FLAME 16K
45		FLAME 17K
31		FLAME 18K
15		FLAME 19K
43		FLAME 20K
18		LEVEL 2
32		LEVEL 3
37		LEVEL 4
21		LEVEL 5
25		RESTORE DUST BOTTOM
41		RESTORE DUST TOP
43		RESTORE SHIELD BOTTOM
15		RESTORE SHIELD TOP
12		RESTORE SWORD BOTTOM
24		RESTORE SWORD TOP
85		RESTORE WEAPONS
96		RETURN LEFT
94		RETURN RIGHT
12		SHIELD LEFT
24		SHIELD MIDDLE
38		SHIELD RIGHT
96		SKILL HELP LEFT
94		SKILL HELP RIGHT
13		SWORD LEFT
25		SWORD MIDDLE
41		SWORD RIGHT
31		TELE LEFT BOTTOM
45		TELE LEFT TOP
14		TELE RIGHT BOTTOM
26		TELE RIGHT TOP

SOLENOID DRIVER LOCATIONS

TRANSISTOR	CONNECTOR	PIN	WIRE	DESCRIPTION
Q11	J6	1	31	BUMPER TOP
Q12	J6	2	32	BUMPER LEFT
Q13	J6	3	34	BUMPER RIGHT
Q14	J6	4	35	BUMPER BOTTOM
Q16	J8	7	27	SLING LEFT
Q15	J8	6	25	SLING RIGHT
Q17	J6	5	36	RESET DTS
Q18	J9	1	51	KICKER LEFT
Q19	J9	2	52	KICKER RIGHT
Q20	J9	3	53	TELEPORT LEFT
Q21	J9	4	54	TELEPORT RIGHT
Q22	J9	6	56	OUTHOLE CONTROLLER
Q38	J9	7	57	RESERVED FOR GERMAN USE
Q39	J9	8	58	OUTHOLE
Q40	J9	11	59	KNOCKER
Q10	J6	7	311	RETURN RIGHT
Q7	J6	8	90	LEFT FLIPPER
Q7	J6	9	95	RIGHT FLIPPER
Q8	J9	10	24	RETURN LEFT

WIRE COLOR CODE

1-RED	6-BROWN
2-BLUE	7-ORANGE
3-YELLOW	8-BLACK
4-GREEN	9-GREY
5-WHITE	0-NO TRACE
J-JUMPER	11-VIOLET
1-FIRST NUMBER-BODY COLOR	
2-SECOND NUMBER-TRACER COLOR	

EXAMPLE: 50-WHITE
51-WHITE/RED

LAMP DRIVER LOCATIONS

LAMP DRIVER

DRIVER	CONNECTOR	PIN	PHASE	WIRE	DESCRIPTION
Q55	J10	16	B	38	ADVANCE LEVEL BOTTOM
Q24	J10	2	B	13	ADVANCE LEVEL TOP
Q36	J13	3	D	84	BRT BOTTOM SKILL
Q35	J13	2	C	83	BRT MILLION
Q51	J13	8	D	93	BRT DRAGON 1
Q66	J13	6	D	87	BRT DRAGON 2
Q66	J13	6	C	87	BRT DRAGON 3
Q36	J13	3	C	84	BRT DROP TARGET
Q35	J13	2	D	83	BRT DUST
Q67	J13	5	D	86	BRT EXTRA BALL
Q65	J11	1	C	48	BRT FLASH LEFT
Q34	J13	1	D	81	BRT FLASH RIGHT
Q65	J11	1	D	48	BRT LEFT SLING
Q67	J13	5	C	86	BRT MIDDLE SKILL
Q34	J13	1	C	81	BRT RIGHT SLING
Q52	J13	13	C	97	BRT SHIELD
Q51	J13	8	C	93	BRT SWORD
Q52	J13	13	D	97	BRT TOP SKILL
Q46	J11	16	B	78	BUMPER BOTTOM
Q60	J10	13	B	36	BUMPER LEFT
Q29	J11	8	B	64	BUMPER RIGHT
Q45	J10	10	B	28	BUMPER TOP
Q61	J11	6	B	62	DRAGON LAIR LEFT
Q30	J11	12	B	72	DRAGON LAIR RIGHT
Q49	J11	9	A	67	DUST 1
Q64	J11	2	A	58	DUST 2
Q33	J11	15	A	75	DUST 3
Q50	J11	7	A	63	DUST 4
Q42	J10	9	A	26	EXTRA LIFE
Q32	J11	14	A	74	FLAME 1K
Q63	J11	3	A	59	FLAME 2K
Q37	J13	4	A	85	FLAME 2X
Q48	J11	10	A	68	FLAME 3K
Q54	J13	11	A	95	FLAME 3X
Q31	J11	13	A	73	FLAME 4K
Q62	J11	4	A	61	FLAME 5K
Q47	J11	11	A	71	FLAME 6K
Q30	J11	12	A	72	FLAME 7K
Q61	J11	6	A	62	FLAME 8K
Q46	J11	16	A	78	FLAME 9K
Q29	J11	8	A	64	FLAME 10K
Q60	J10	13	A	36	FLAME 11K
Q45	J10	10	A	28	FLAME 12K
Q28	J10	6	A	21	FLAME 13K
Q59	J10	14	A	37	FLAME 14K
Q44	J10	12	A	32	FLAME 15K

DRIVER	CONNECTOR	PIN	PHASE
Q27	J10	5	A
Q58	J10	19	A
Q43	J10	11	A
Q26	J10	4	A
Q57	J10	18	A
Q27	J10	5	B
Q44	J10	12	B
Q59	J10	14	B
Q28	J10	6	B
Q41	J10	8	B
Q56	J10	17	B
Q57	J10	18	B
Q26	J10	4	B
Q23	J10	1	B
Q70	J10	7	B
Q37	J13	4	B
Q53	J13	12	A
Q68	J13	10	A
Q23	J10	1	A
Q70	J10	7	A
Q55	J10	16	A
Q53	J13	12	B
Q68	J13	10	B
Q24	J10	2	A
Q41	J10	8	A
Q56	J10	17	A
Q43	J10	11	B
Q58	J10	19	B
Q25	J10	3	B
Q42	J10	9	B

GLOSSARY OF UNIQUE TERMS AND ABBREVIATIONS

The following list of unique terms and abbreviations are used in the DUNGEONS & DRAGONS Operating Manual. Service Technicians and Operators should note that more than one description may apply to a particular term or abbreviation. Also, more than one term or abbreviation may apply to a particular description. Either way, the Technician or Operator need only be concerned with correctly matching the term or abbreviation with the corresponding description.

TERM/ABBREVIATION	DESCRIPTION
A, AD, ADDR	Address
AX	Axial
BATT	Battery
BD, BRD	Board
BR	Bridge Spacer
C, CAP, CP	Capacitor, Common
CER	Ceramic
COM	Common
CON, CONN	Connector
CPURST	CPU Reset
CR	Diode
CRBN	Carbon
D	Data, Digital Display Module, Diode, Zener Diode
DISPLAY	Gas Discharge Display
F, FU	Fuse
FB	Ferrite Bead
FC	Fuse Clips
FL	Filter
HS	Heatsink
ICS, XU	I.C. Socket
INS	Silicon Pad Thermal Washer
J	Connector, Plug
JW	Jumper Wire
K	Relay
L	Inductor
LED	Infrared Light Emitting Diode
MH	Mechanical Hardware
MTG	Mounting
MTR	Meter
N.C.	Normally Closed
N.O.	Normally Open
PB	Push Button
PWR	Power
Q	Transistor, Silicon Controlled Rectifier (SCR), Darlington
R, RES, RM	Resistor
RTN	Return
S	Sound Module
SND	Sound
SW	Switch
T	Transformer
TP	Test Point, Test Loop
VA	Varistor
VR	Potentiometer, Varistor
XSTR	Transistor
XTAL, Y	Crystal

BALLY/MIDWAY'S DUNGEONS & DRAGONS

#H06

ROM/EPROM PART NUMBERS

UNPROGRAMMED CONTROL BOARD A084-91786-G000
PROGRAMMED CONTROL BOARD A084-91786-AH06

POS.	MIDWAY PART NUMBER
U2	H06A-12601-0000
U3	H06A-12602-0000

JUMPERS	IN	OUT
JW1		X
JW2	X	
JW3		X
JW4	X	
JW5		X
JW6	X	
JW7		X
JW8		X
JW9	X	
JW10	X	
JW11		X

UNPROGRAMMED SOUNDS DELUXE A084-91864-C000
PROGRAMMED SOUNDS DELUXE A084-91864-AH06

POS.	MIDWAY PART NUMBER
U11	H06A-12603-0000
U12	H06A-12604-0000
U13	H06A-12605-0000
U14	H06A-12606-0000

JUMPERS	IN	OUT
JW1	X	
JW2	X	
JW3		X
JW4	X	
JW5		X
JW6		X
JW7	X	
JW8-JW12	X	

M051-00H06-A008	REVISIONS
9-30-87	RELEASE FOR PRODUCTION